

Smart Clean Care

SPTBCARE

1 Litre, 5 Litres & 15 Litres



Description

Smart Clean Care is a modified acrylic emulsion paint, specially formulated for easy care of home owners with Smooth Elegant Classic Matt Finishes for an air of elegance for all wall finishes. It is a premium quality decorative paint with high durability, tough and scrubable, tested and proven with more than 10,000 scrubs with

Sheen Wet Abrasion Scrub Tester. It is formulated with anti-mould and anti-fungus properties to inhibit the growth of mould and fungus, creating a healthier living environment. It is for all normal interior wall and ceiling surfaces. Ideal for areas like bathroom, living room, kitchen, bedroom, office partition and decorative glass fiber fabric wall covering. Washable and scrubable.

Usage

For decoration and protection of wall, ceiling, plaster, brickwork and cement board for a Smooth and Elegant Classic Matt finish.

Composition

| | | |
|--------------|---|--|
| Pigment | : | Lightfast Non – Lead Pigments and Mineral Extenders. |
| Binder | : | Acrylic Emulsion. |
| Volume Solid | : | White 33% (Nominal), others colours will vary. |
| Diluent | : | Water |

Properties

| | | |
|----------------------|---|---|
| Finishing | : | Smooth Elegant Classic Matt Finish. |
| Colour | : | Refer to color card. |
| Theoretical Coverage | : | 10 - 12m ² / Litre (actual coverage dependent on substrate condition.) |
| Drying Time | : | Touch dry – 30 to 60 minutes. *Dependent on temperature and humidity. |
| Recoating Interval | : | 1 to 2 hours. |

Application Method

| | | |
|------------------------|---|--|
| Brush | : | For normal use thinning is not necessary. |
| Roller | : | For normal use thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application. |
| Conventional Air Spray | : | Thin with 10 – 20% by volume with water. |
| Airless Spray | : | For normal use thinning is not usually necessary. Can be thin with 5 – 10% by volume with water to assist application. |

Surface Preparation

General / New

Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. To have better finish rubbed down surface using suitable abrasive and dust off. If after thorough preparation surface remain powdery, or suffer from alkali attack, for best effect seal with 1 coat of Smart Wall Sealer.

Previously Painted Surface

Remove all loose, defective and unstable paint film or powdery residues by thorough brushing and scraping. Make good minor defects and cracks with suitable grade filler.

Painting Guide

| Surface Condition | Primer (To paint 1 coat) | Finish (To paint 2 - 3 coats) |
|---------------------|---|-------------------------------|
| Powdery Surface | <ul style="list-style-type: none"> • Smart High Performance Sealer 900 (Solvent Base) • Smart Green Sealer 850 • Smart Wall Sealer 800 • Smart GP Wall Sealer 400 | Smart Clean Care |
| Alkali/ New Surface | <ul style="list-style-type: none"> • Smart High Performance Sealer 900 (Solvent Base) • Smart Wall Sealer 800 • Smart Green Sealer 850 | Smart Clean Care |

Composition / Information on Ingredients

| Component | % by wt |
|------------------|---------|
| Emulsion Polymer | < 18% |
| Pigment | < 50% |
| Additive | < 2% |
| Water | < 30% |

Hazard Identification

Not classified

First Aid Measures

Emergency and first aid procedures :

If overcome by vapors, remove to fresh air and if breathing stopped, give artificial respiration. Keep individual calm. Call a physician. If eye contact occurs, flush with water for at least 15 minutes and call a physician. For skin contact, wash thoroughly with soap and water. If swallowed, do not induce vomiting. Drink a glass of water and consult physician IMMEDIATELY.

Physical and Chemical Properties

| | |
|--|--------------------------------------|
| Appearance / colour | : Viscous liquid with various colour |
| Solid | : <60% (depends on colour) |
| Specific gravity @ 25oc | : 1.00 – 1.60 (depends on colour) |
| *Boiling point | : 100 oC |
| *Melting point | : 0 oC |
| *Vapour pressure (air = 1) | : >1 |
| *Vapour density (101.3 kpa / air = 1) | : >1 |
| Evaporation rate (n – butyl ether = 1) | : <1 |
| Solubility | : Miscible with water |
| Odour | Mild |
| *Properties of water | |

Fire Fighting Measures

| | |
|----------------------------------|---|
| CLASSIFICATION | : Not Combustible |
| *FLASH POINT | : NA |
| *EXPLOSIVE LIMITS (% BY VOLUME): | |
| • LEL | : NA |
| • UEL | : NA |
| FIRE EXTINGUISHING MEDIA | : Foam, CO2, Dry Powder, sand |
| FIRE FIGHTING PROCEDURES | : Respiratory protection is required for fire fighting personnel. Do not breathe fumes. Stay upwind, if possible. |
| *properties of solvent used | |

Accidental Release Measures

- Personal precautions : Use appropriate safety equipment. For additional information, refer to Section 8, Personal Protection information.
- Environmental precautions : Prevent the product from escape into soil, watercourses or drainage systems.
- Cleaning methods : Eliminate source of ignition. Contain area and keep public away. Recover free liquid by pumping or scooping with shovel into separate container. Use sawdust, sand, earth or other absorbent to prevent material flow. Prevent liquid from entering sewers, watercourse or low areas. Dispose in accordance with local regulation.

Handling and storage

Keep container closed when not in use. Do not handle or store near open flame, heat, sparks, or strong oxidants. Adequate ventilation required. Avoid inhalation of vapours and contact with skin and eyes. Do not keep product for a long time (>2 years). Keep good house-keeping.

Exposure Controls / Personal Protection

- Respiratory Protection : Use approved respiratory protection such as air supplied mask if used in enclosed spaces.
- Ventilation : Sufficient ventilation should be provided during application.
- Protective gloves : Chemically resistant gloves
- Eye protection : Chemical splash-proof goggles or face shield

Stability and Reactivity

- Conditions to avoid : Heat, spark, open flame and static charge build-up
- Incompatibility (materials to avoid) : Strong oxidizing agents
- decomposition products : Carbon monoxide and carbon dioxide

Toxicological Information

- Skin contact : Prolonged and repeated contact may cause slight skin irritation.
- Eye contact : Prolonged and repeated contact may cause slight temporary eye irritation.
- Inhalation : Prolonged and repeated may cause respiratory irritation. Signs and symptoms of excessive exposure may include headache, or vomiting.

Effects of over exposure : High vapour and spray mist can be irritating to the eyes, skin and the respiratory tract. Excessive inhalation can cause headache, nausea, dizziness or irritation to the respiratory tract and may have other central nervous system effects. Ingestion can cause lungs, kidney and/or liver damage. Overexposure can cause irreversible eye burns and damage. Skin and respiratory sensitization and allergic reaction such as rash, hives or asthma can occur.

Ecological Information

No ecological studies have been carried out on this product.

Disposal Considerations

If possible recover the product, otherwise dispose by incinerate or land fill must be in compliance with all local laws and regulation.

Transport information

| | | |
|-----------------|---|---------------|
| Road (adr) | : | Not Regulated |
| rail (rid) | : | Not Regulated |
| air (icao/iata) | : | Not Regulated |
| sea (imo/imdg) | : | Not Regulated |

Regulatory Information

Regulatory information in country or region with regards to this product should be observed.

Other Information

All information appearing herein is based on our present state of our knowledge. However the information in this MSDS may not be valid for such material used in combination with any other materials or in any process. No representation, warranty or guarantee is made as to its accuracy, reliability or completeness. We do not accept liability for any loss or damage that may occur from the use of this information.

Company Identification

| | | |
|---------------|---|---|
| Manufacturer | : | Smart Paints (M) Sdn. Bhd. 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang, 81800 Ulu Tiram, Johor, Malaysia |
| Telephone No. | : | +607-289 2855 |
| Email | : | info@smart-paints.com |
| | | Fax No. : +607-861 5055 |