



Smart Cool Weather

SPCW

1 Litre, 5 Litres, 15 Litres & 20 Litres



Description

Smart Cool Weather Paint is a premium quality, 100% full acrylic based emulsion paint. It is specially formulated for the tropics with excellent weathering properties, fungus and algae resistance. Smart Cool Weather Paint finishes have excellent alkali resistance, adhesion and durability. It is formulated to provide at least 6 years protection against fungus and algae growth with correct application.

Usage

For decoration and protection of previously painted or new exterior walls for a long lasting aesthetic finish.

Composition

Pigment	:	Lightfast Non – Lead Pigments and Mineral Extenders.
Binder	:	100% Full Acrylic Emulsion.
Volume Solid	:	White 40% (Nominal), others colours will vary.
Diluent	:	Water

Properties

Finishing	:	Smooth Matt Finish.
Colour	:	A wide range of colours. Please refer Smart Cool Weather Colour Card.
Theoretical Coverage	:	11 – 13 m ² /Litre
Drying Time	:	Touch dry – 15 to 30 minutes. Hard dry – 1 to 2 hour. <small>*Dependent on temperature and humidity.</small>
Recoating Interval	:	1 to 2 hours.

Application Method

Brush	:	For normal use thinning is not necessary.
Roller	:	For normal use thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application.
Conventional Air Spray	:	Thin with 10 – 20% by volume with water and adjust to requirement.
Airless Spray	:	Thinning is not necessary. Can be thin 5 - 10% by volume with water to assist application.

Surface Preparation

- Remove all loose, defective paint or powdery residues by wire brushing, scraping, or high pressure water jet. Treat any areas affected by fungus growth with fungicidal wash solution and left dry before painting. Repair cracks, uneven surfaces with putty or suitable fillers. Smoothen the putty areas with sandpaper. Make sure all surfaces are dry before painting. Avoid painting when the moisture content of the walls are still high. (Recommended painting specification requires the moisture content of the walls to be below 16% measured by Protimeter)

Painting Guide

Surface Condition	Sealer (1 coat)	Finish (1 - 2 coats)
Powdery Surface	<ul style="list-style-type: none"> • Smart High Performance Sealer 900 (Solvent Base) • Smart Green Sealer 850 • Smart Eco Sealer • Smart Wall Sealer Super 5400 	Smart Cool Weather
Alkali/ New Surface	<ul style="list-style-type: none"> • Smart High Performance Sealer 900 (Solvent Base) • Smart Green Sealer 850 • Smart Eco Sealer • Smart Wall Sealer Super 5400 	Smart Cool Weather

Company Identification

Manufacturer : Smart Paint Manufacturing Sdn. Bhd.
 No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,
 81800 Ulu Tiram, Johor, Malaysia
 Telephone No. : +607-863 9855 (Hunting Line) Fax No. : +607-861 5055
 Email : info@smart-paints.com