

# 2K Water-Based Epoxy Damp Sealer (Part B) Epoxy Solvent-Free Based Hardener 0.85 Litre (Part B)

Version No. : 3.2.24

Issue Date: 11.04.2023 Safety Data Sheet according to CLASS requirement



Product Identifier	
Product Name	Smart Paints 2K Water-Based Epoxy Damp Sealer (Part B)
Product Code	SPEPDS-PART B
Chemical Name	Not Applicable
Chemical Formula	Not Applicable
Other means of Identification	Epoxy Solvent Free
CAS Number	Not Applicable
Relevant use of the chemical and restriction	
Relevant identified uses	Use according to manufacturer's directions
Details of manufacturer / importer	
Registered Company Name	SMART PAINT MANUFACTURING SDN BHD (1031014-A)
Address	No. 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang, 81800 Ulu Tiram, Johor, Malaysia.
Telephone	+607-863 9855
Fax	+607-861 5055
Email	info@smart-paints.com
Web	http://www.smart-paints.com
Emergency telephone number	
Association / Organisation	Not Applicable
Emergency telephone number	Not Applicable
Other emergency telephone number	Not Applicable
ECTION 2 HAZARDS IDENTIFICATION	
classification of the substances or mixture	
GHS Classification	Health Hazard
	Serious Eye Damage/ Eye Irritation - Category 2A
	Skin Corrosion/irritation - Category 2
	Environment Hazard
	Hazardous To The Aquatic Environment – Chronic Hazard - Category 3
abel elements	
GHS label elements	
Signal word	
	Warning

Signal word	Warning
Hazard statement(s)	
H316	May cause mild skin irritating
H317	May cause allergic skin reaction.
H320	May cause eye irritating.

Precautionary statement(s)	
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P332 + 337+ 350+ 313	If skin/eyes irritation occurs, wash with plenty of soap and water and get medical advice/ attention.
P202	Do not handle until all safety precautionary have been read and understood.
P281	Use personal protective equipment as required.
P264	Wash thoroughly after handling.
P272	Contaminated work clothing shall not be allowed out of the workplace.
P273	Avoid release to the environment.

SECTION 2 HAZARDS IDENTIFICATION	
Precautionary statement(s) Response	
P303+P361+P353	IF ON SKIN (or hair) : Remove/take off immediately all contaminated clothing. Rinse skin with water / shower.
P301+P310 P331	IF SWALLOWED : Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.
P308+P313	IF exposed or concerned : Get medical advice / attention.
P304+P341	IF INHALED : If breathing is difficult, remove victim to fresh air and keep at rest.
P342+P311	If experiencing respiratory symptoms : CALL a POISON CENTER or doctor / physician .
P302+P352	IF ON SKIN : Wash with plenty of water and soap.
P321	Specific treatment (see information on this label).
P332+P313	If skin irritation occurs : Get medical advice / attention
P362	Take off contaminated clothing and was before reuse.
P304+P340	IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P333+P313	If skin irritation or rash occurs : Get medical advice / attention.
P363	Wash contaminated clothing before reuse.
Precautionary statement(s) Storage	
P403+P235 P405 P403+P233	Store in a well - ventilated place. Keep cool. Store in locked up. Store in a well - ventilated place. Keep container tightly closed.
Precautionary statement(s) Disposal	
P501	Dispose of content/ container to appropriate waste site or reclaimer in accordance with local or national regulations.

# SECTION 3 COMPOSITION / INFORMATION OF INGREDIENTS

CAS number	% [weight]	Ingredient
-	<10	Diluent
-	<90	Resin

Description of first aid measure           Eye contact         • Check or and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelid open. Do not use an eye ointment. Seek for medical attention.           Skin contact         • Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an exiting dermatitis condition. Remove contaminated clothing – launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abbrasive soap. Get medical attention if redness or irritation occurs.	SECTION 4 FIRST AID MEASURES	
<ul> <li>15 minutes, keeping eyelid open. Do not use an eye ointment. Seek for medical attention.</li> <li>Skin contact         <ul> <li>Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an exiting dermatitis condition. Remove contaminated clothing – launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abbrasive soap. Get medical attention if redness or</li> </ul> </li> </ul>	Description of first aid measure	
dermatitis condition. Remove contaminated clothing – launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abbrasive soap. Get medical attention if redness or	Eye contact	
	Skin contact	dermatitis condition. Remove contaminated clothing – launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abbrasive soap. Get medical attention if redness or

#### SECTION 5 FIREFIGHTING MEASURES

#### Suitable Fire Extinguishing Media :

Small fire : Use dry chemical. Foam or CO2. : Use water spray. Fog or foam. Water or foam may cause frothing. Large fire

#### Special Protective Actions For Fire Fighters:

Cool container in water spray in order to prevent pressure build-up, auto ignition or explosion. Avoid flushing spilled material into sewers, stream or other bodies of water. For small outdoor fires, portable fire extinguishers may be used, and self contained breathing apparatus (SCBA) may not be required. Respiratory and eye protection are required for fire fighting personnel.

#### Specific Hazards Arising From The Chemical :

Static discharge, material can accumulate static charges which can cause an incendiary electrical discharge. "Empty" containers retain product residue (liquid and/or vapour) and can be dangerous. DO NOT pressurize, cut. Weld braze, solder, drill grind, or expose such containers to heat, flame sparks, static electricity, or other sources of ignition ; they may explode and cause injury or death.

#### SECTION 6 ACCIDENTAL RELEASE MEASURES

#### Personal Precautions, Protective Equipment And Emergency Procedure

#### Eye /skin protection :

Where there is potential for eye contact, wear chemical goggles and have eye flushing equipment immediately available. Wear appropriate protective clothing and chemical resistant gloves to prevent skin contact. Wear a face shield and chemical resistant clothing such as rubber apron when splashing is likely. **Respiratory Protection :** 

Use JKKP/NIOSH approved respiratory protection (full face piece recommended) when exposure limits are exceeded.

#### Ventilation :

Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. If practical, use local mechanical exhause ventilation at source of air contamination such as open process equipment.

#### Environment Precaution

Flammable liquid. Ventilate. Eliminate all sources of ignition. Prevent additional discharge of material. For small spills implement cleanup procedure; for large spills implement cleanup procedure and if in public area, keep public away and advice authorities, provide suitable personal protective, dike and contain spill with inert material (sand, earth, etc) and transfer liquid and solid separately to container for recovery or disposal. Report as per regulatory or disposal. Do not use combustible material such as sawdust. Report as per regulatory equipment.

#### Methods And Materials For Containments And Clean Up

For small liquid spills (<1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residue to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose to all salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Remove contaminated soil and dispose of safely.

#### SECTION 7 HANDLING AND STORAGE

#### Precautions For Safe Handling

Avoid smoking and use of open ire. Avoid inhalation of vapours and contact with skin and eyes. Observe good industrial practices

ACGIH TLV-TWA

ppm

#### Condition For Safe Storage ,including Any Incompatibilities

Store in tightly closed original container in well-ventilated area. Avoid expose to direct sunlight.

#### SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Control Parameters/ Occupational Limits

Ingredient/Bahan

mg/m3

mg/m3

**OSHA PEL-TWA** 

ppm

#### APPROPRIATE ENGINEERING CONTROL MEASURES

If user operations generate dust, fumes, gas, vapours or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emission from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### PERSONAL PROTECTION Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended : Full mask with type Cartridge filter.

#### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products I a risk assessment indicates this is necessary. After contamination with product change the gloves immediately and dispose of them according to relevant national and local regulations

#### Eye protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Recommended : Safety glasses with side-shields.

#### Skin/ Body Protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended : Wear protective clothing

# SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance / colour	Liquid / Clear
Pigment	-
Solid	100.0%
Specific Gravity (@ 25°C)	1.13
Viscosity (Ku)	Not applicable
*Boiling Point	Not applicable
*Melting Point	Not applicable
*Vapour Pressure (@ 20°C)	Not applicable
Vapour Density (101.3 kPA / air=1)	Not applicable
Evaporation Rate (n - Butyl Ether=1)	Not applicable
Solubility	Insoluble in water
Odour	Mild

#### SECTION 10 STABILITY AND REACTIVITY

#### REACTIVITY

No dangerous reaction known under condition of normal use.

#### CHEMICAL STABILITY

Stable under normal temperature conditions and recommended use.

#### POSSIBILTY OF HAZARDOUS REACTION

Under normal conditions of storage and use, hazardous reaction will not occur.

#### CONDITIONS TO AVOID

Heat, flame , sparks. Nitric acid, sulfuric acid, strong oxidizing agents. Electrostatic accumulation hazard? If Yes, use proper grounding procedure.

# HAZARDOUS DECOMPOSITION PRODUCTS

When expose to high temperature, may produce hazardous decomposition products such as Carbon monoxide ,carbon dioxide, smoke and oxides of nitrogen

#### SECTION 11 TOXICOLOGY INFORMATION

There is no data available on the product itself. Toxicological information of hazardous ingredients :

Acute toxicity	: Not Classified
Skin corrosion/ irritation	: Dry skin
Serious eye /damage irritation	: Risk of serious damage eyes
Respiratory sensitization	: May lead to dermatitis
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not Classified
Reproductive toxicity	: No data available
Specific target organ toxicity (single exposure)	: No data available
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: No data available
Symptoms/injuries after inhalation	: No data available
Symptoms/injuries after skin contact	: No data available
Symptoms/injuries after eye contact	: Not Classified
Symptoms/injuries after eye ingestion	: Not Classified
Chronic symptoms	: Not Classified

### SECTION 12 ECOLOGICAL INFORMATION

# Ecotoxicity

No data available.

#### Persistence And Degradability No information available.

Bioaccumulative Potential Has the potential to bioaccumulate.

#### Mobility In Soil

Floats on water. Adsorbs to soil and has low mobility.

#### Other Adverse Effects

Do not allow product to reach ground water, water course or sewage system.

# SECTION 13 DISPOSAL INFORMATION

#### Waste Disposal :

Recover or recycle if possible. Otherwise dispose in accordance with all applicable with all applicable national environment laws and regulations.

### Product Disposal:

This product when dispose of in its unused and uncontaminated state should be treated as a hazardous waste.

#### **Container Disposal :**

Drain container thoroughly. Rinse three times with suitable solvent. Treat rinsing as for product disposal. After draining, vent in a safe place away from sparks and fire. Send drum recoverer or metal reclaimer. Residue may cause an explosion hazard. Do not pincture, cut or weld uncleaned drums. Keep container labelled until cleaned and then remove or deface labels.

### SECTION 14 TRANSPORT INFORMATION

Transport to be in accordance with ADR/RID for road/rail, IMDG for sea and IATA for air.

#### LAND TRANSPORT

Classified as Dangerous Goods by the criteria of the European Agreement concerning the international carriage of Dangerous Goods (ADR) by Road & Regulations concerning the international carriage of Dangerous Goods (RID) by Rail.

#### UN Number: 1263

Proper shipping name : Paint (including paint, lacquer,enamel, stain, shellac, varnish, liquid filler and liquid lacquer base ) or paint related material (including paint thinning or reducing compound.

Class: 3

Packaging Group: III

#### SEA TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG) for the transport of Sea.

#### UN Number: 1263

Proper shipping name : Paint (including paint, lacquer,enamel, stain, shellac, varnish, liquid filler and liquid lacquer base ) or paint related material (including paint thinning or reducing compound.

#### Class : 3 Packaging Group: III

#### Marine Pollutant: No

SEA (Annex II of MARPOL 73/78 and the IBC Code)/ LAUT (Annex II of MARPOL 73/78 dan the IBC Code) : Not Applicable

#### AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for the transport by Air.

#### UN Number: 1263

Proper shipping name : Paint ( including paint, lacquer,enamel, stain, shellac, varnish, liquid filler and liquid lacquer base ) or paint related material (including paint thinning or reducing compound. Class: 3

Packaging Group: III

#### SECTION 15 REGULATORY INFORMATION

Applicable national regulations :

a) OHSA 1994 and relevant regulation

b) Factories and Machinery Act 1967 and relevant regulations

c) Environment Quality Act 1967 and regulations.

d) Pesticide Act 1974 and regulations

e) Occupational Safety and Health (Classification, Labelling And Safety Data Sheet of Hazardous Chemicals) Reg 2013 f) Industry Code Of Practice (On Chemicals Classification And Hazard Communication

#### SECTION 16 OTHER INFORMATION

Date of preparation: 11-04-2023 Date of revision: -
Version: 01
ABBREVIATION/SINGKATAN
ACGIH American Conference of Governmental Industrial Hygienists
TLV Threshold limit value
TWA Time-Weighted Average
OSHA Occupational Safety and Health Administration
PEL Permissible Exposure Limit
LD50 Lethal Dose
LC50 Median Lethal concentration
IACR International Agency for Research in Cancer
CAS Registry Numbers Chemical Abstracts Service Registry Numbers
ICOP Industry Code Of Practice on Chemical Classification and Health approved by Minister under section 37 of the Act
C Ceiling Limit
CEIL Ceiling Limit airborne concentration
STEL Short Term Exposure Limit
DNA Data Not Available
N/R Not Regulated
Disclaimer
All information appearing here in is based on our present state of our knowledge. However the information in this SDS may not be valid for such material
used in combination with any other materials or in any process. No representation, warranty or guarantee is made as to its accuracy, reliability or
completeness. We do not accept liability for any loss or damage that may occur from the use of this information.