



## Smart Easy Wash

SPEASW / SPTBEASW

1 litre, 5 litres, 15 litres, 18 litres

### Description

**Smart Easy Wash** is a premium eco and health friendly interior paint specially formulated for easy cleaning. This low odour, low VOC formula provides a tough and extremely smooth surface for easy cleaning. Stains can be easily wiped off, so the egg-shell finish walls are always clean and easy to maintain. Smart Easy Wash is formulated to resist spattering to help keep tools and jobsite clean, application will always flow smooth for perfect finishing.

### Usage

For decoration and protection of wall, ceiling, plaster, brickwork and cement board for a Smooth and Elegant Classic mid-sheen finish.

### Composition

Pigment	:	Lightfast non-lead pigments and mineral extenders
Binder	:	Acrylic based emulsion.
Volume Solid	:	White 38% (Nominal), other colours will vary.
Diluent	:	Water.

### Properties

Finishing	:	Classic Mat Washable Paint
Colour	:	Refer to color card.
Theoretical Coverage	:	10 - 12m <sup>2</sup> / Litre (actual coverage dependent on substrate condition.)
Drying Time	:	*Touch dry – 15 minutes. *Dependent on temperature and humidity.
Recoating Interval	:	1 to 2 hours.

### Application Method

Brush	:	For normal use thinning is not usually necessary.
Roller	:	For normal use thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application.
Conventional Air Spray	:	Thin with max 10 – 20 % by volume with water
Airless Spray	:	For normal use thinning is not usually necessary. Can be thin with 5 – 10% by volume with water to assist application.

## Surface Preparation

### General/New

Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. To have better finish rubbed down surface using suitable abrasive and dust off. If after thorough preparation surface remain powdery, or suffer from alkali attack, for best effect seal with 1 coat of Smart Green Sealer 850.

### Previously Painted Surface

Remove all loose, defective and unstable paint film or powdery residues by thorough brushing and scraping. Make good minor defects and cracks with suitable grade filler.

## Painting Guide

Substrate	Primer (1coat)	Finish (2 – 3 coats)
Powdery surface	Smart Green Sealer 850 Smart Eco Sealer Smart Wall Sealer 900 Smart Wall Sealer Super 5400	Smart Easy Wash
Alkali/ New Surface	Smart Green Sealer 850 Smart Eco Sealer Smart Wall Sealer 900 Smart Wall Sealer Super 5400	Smart Easy Wash

## Company Identification

Manufacturer : Smart Paint Manufacturing Sdn. Bhd.  
No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,  
81800 Ulu Tiram, Johor, Malaysia

Telephone No. : +607-863 9855 (Hunting Line) Fax No. : +607-861 5055

Email : info@smart-paints.com