



Zero VOC



Pure Water

- Zero VOC Paint
- APEO Free
- Super Low Odour
- No Formaldehyde
- No Heavy Metal
- Deionized Water Product
- Luxury Sheen Finish
- Premium Washable Paint
- Smart Flow Technology®
- Tested by SetSCO Singapore



**ECO-SILK**  
Zero VOC Luxury Sheen Interior Paint



Reserve The Best  
For Your Love....



**SMART ECO-SILK**

SMART ECO-SILK 是精心研发的超低漆味。不含APEO及挥发性有机化合物的室内高级乳胶漆。其珍珠般的亮丽光泽能使墙面呈现奢华般的效果感以及营造健康的家居环境。此配方也具备了持久亮丽及耐洗刷功能。SMART ECO-SILK 最适合用于保护室内墙面及天花板表面。

**表面处理**

确保表面干净及彻底干透。绝无松散的污垢、油脂或蜡迹。同时，也必须把已损坏的表面用 putty filla 修补好。欲取得最佳效果，请先涂上一层 SMART ECO-SEALER，然后涂上两层 SMART ECO-SILK。

**施工资料**

手触干度：视气温和湿度而定。  
 覆涂层涂：相隔1到2小时。  
 覆涂面积：每公升10-13平方米。  
 层数：两层



**用法**

搅拌用具：使用前需彻底搅均。可用漆扫，油漆滚筒涂或喷射。  
 调稀：通常不必调稀。如果需要调稀，可用不超过10%的清水进行稀释。  
 清理：喷漆工作完成后，即刻用清水洗净工具。

**SMART ECO-SILK**

SMART ECO-SILK adalah cat emulsi yang dirumus khas dengan sebatian organik yang kurang bau, tanpa mengandungi APEO dan VOC yang dapat memberikan tempat penginapan yang mesra alam. Ia menyediakan cat kemasan dinding yang berkilat dan mewah serta dapat melindunginya. Selain daripada itu, ia juga memberi permukaan yang tahan lasak dan boleh dicuci. Rumusan ini amat sesuai untuk dinding dalaman dan permukaan siling.

**Penyediaan Permukaan**

Pastikan permukaan yang hendak dicat bersih, dinding kering sepenuhnya dan bebas daripada segala bahan cat yang menyerpih, kotoran, minyak atau lilin. Membaiki permukaan yang rosak atau retakan halus dengan Putty Filla sebelum menyapu cat. Untuk hasil yang cemerlang, sapu satu lapisan SMART ECO-SEALER diikuti dengan 2 lapisan SMART ECO-SILK. Biarkan selama 1-2 jam masa pengeringan di antara lapisan cat.

**Data Penggunaan**

Tempoh Kering : Bergantung kepada suhu dan kelembapan  
 Tempoh Lapisan Semula : 1 - 2 jam  
 Liputan Teori : 10-13 m<sup>2</sup> per/ litre  
 Jumlah Lapisan : 2 lapisan.



**Cara Penggunaan**

Cara Penggunaan : Kacau sehingga sekata sebelum menggunakannya. Cat ini boleh disapu dengan berus, penggelek atau penyembur.  
 Pencapaian : Untuk kegunaan biasa, pencairan lazimnya tidak diperlukan. Jika perlu, cairkan dengan maksimum 10% air.  
 Liputan Teori : Cuci perkakas dengan air bersih sebaik sahaja selesai kerja.

**SMART ECO-SILK**

SMART ECO-SILK is a specially formulated Zero VOC, APEO Free and low odour emulsion paint that provides a healthy living environment for the family. It provides a high sheen wall finish that is able to enhance the indoor surface with luxurious feel while protecting the wall at the same time. The paint film is highly durable and washable which is suitable for interior wall and ceiling.

**Surface Preparation**

Ensure wall surface to be painted in is clean, thoroughly dry and free from all defects or poor adhering material like dirt, grease and wax. Repair surface defects or hairline crack by using Putty Filla before painting. For best results, apply 1 coat of SMART ECO-SEALER and followed by 2 coats of SMART ECO-SILK. Allow about 1-2 hours drying between coats.

**Application Data**

Touch Dry : Dependent on temperature and humidity  
 Recoat : 1-2 hours.  
 Coverage : 10-13 m<sup>2</sup> per/ litre  
 No. of coat : 2 coats.



**Direction For Use**

Application : Stir well before use. Application can be carried out by using brush, roller or spraying.  
 Thinning : Use directly or dilute with a maximum of 10% water.  
 Cleaning Up : Clean all equipment with clean water immediately after use.

FOR BETTER PAINTING RESULT  
WE STRONGLY RECOMMENDED

1 COAT OF  
SMART  
ECO-SEALER



+

2 COAT OF  
SMART  
ECO-SILK















## Premium Washable Paint



### Shade Of White



The colours on this card are as close to the actual colours as modern printing techniques allow.