



Smart Eco-Ultra Silk

SPTBECS

1 Litre, 5 Litres & 15 Litres

Description

SMART ECO-ULTRA SILK is a specially formulated Zero VOC, APEO Free and low odour emulsion paint that provides a healthy living environment for the family. It provides a high sheen wall finish that is able to enhance the indoor surface with luxurious feel while protecting the wall at the same time. The paint film is highly durable and washable which is suitable for interior wall and ceiling.

Usage

For decoration and protective of wall, ceiling, plaster, brickworks, cement board for a Luxury Decorative Mid Sheen Finish. Easily maintained by cleaning with a damp cloth.

Composition

Pigment	:	Lightfast Non – Lead Pigments and Mineral Extenders.
Binder	:	Vinyl Polymer
Volume Solid	:	White 38% (Nominal), other colours will vary.
Diluent	:	Water.

Properties

Finishing	:	Mid Sheen Luxury Finish.
Colour	:	A wide range of colours. Please refer Smart Vinyl Glo Colour Card.
Theoretical Coverage	:	10 - 12 m ² /Litre
Drying Time	:	*Touch dry – 30 to 60 minutes. *Dependent on temperature and humidity.
Recoating Interval	:	1 to 2 hours.

Application Method

Brush	:	For normal use thinning is not necessary.
Roller	:	For normal use thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application.
Conventional Air Spray	:	Thin with 10 – 20% by volume with water and adjust to requirement.
Airless Spray	:	Thinning is not necessary. Can be thin 5 - 10% by volume with water to assist application.

Surface Preparation

Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease and wax. (To have a better finish, rub down surface using suitable abrasive and dust off.) If after thorough preparation surface remains powdery, for best effect seal with 1 coat of Smart Eco Sealer. If the surface suffers from alkali attack, it is best recommended to seal with 1 coat of Smart Eco Sealer.

Painting Guide

Substrate	Primer (1coat)	Finish (1 – 3 coats)
Powdery Surface	Smart Eco Sealer Smart Wall Sealer Super 5400	Smart Eco UltraSilk
Alkali/ New Surface	Smart Eco Sealer Smart Wall Sealer Super 5400	Smart Eco UltraSilk

Company Identification

Manufacturer : Smart Paint Manufacturing Sdn. Bhd.
 No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,
 81800 Ulu Tiram, Johor, Malaysia
 Telephone No. : +607-863 9855 (Hunting Line) Fax No. : +607-861 5055
 Email : info@smart-paints.com