

Smart Eco Wash

SPTBEW

1 Litre, 5 Litres & 15 Litres



Description

Smart Eco Wash is a premium eco and health friendly interior paint specially formulated for easy cleaning. This low odour, near zero VOC formula provides a tough and extremely smooth surface for easy cleaning. Stains can be easily wiped off, so the egg-shell finish walls are always clean and easy to maintain. **Smart Eco Wash** is formulated to resist spattering to help keep tools and jobsite clean, application will always flow smooth for perfect finishing.

Note : Volatile organic compound (VOC) are air borne chemicals harmful to health and the environment.

Usage

For decoration and protection of wall, ceiling, plaster, brickwork and cement board for a Smooth and Elegant Classic egg shell finish.

Composition

Pigment	:	Lightfast non-lead pigments and mineral extenders.
Binder	:	Vinyl Acetate - Ethylene Emulsion.
Volume Solid	:	White 42% (Nominal), other colours will vary.
Diluent	:	Water

Properties

Finishing	:	Smooth Elegant Classic Egg Shell Finish.
Colour	:	Refer to color card.
Theoretical Coverage	:	10 - 13m ² / Litre (actual coverage dependent on substrate condition.)
Drying Time	:	Touch dry – 15 minutes *Dependent on temperature and humidity.
Recoating Interval	:	1 to 2 hours.

Application Instruction:

Brush	:	For normal use thinning is not usually necessary.
Roller	:	For normal use thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application.
Conventional Air Spray	:	Thin with max 10 – 20 % by volume with water.
Airless Spray	:	For normal use thinning is not usually necessary. Can be thin with 5 – 10% by volume with water to assist application.

Surface Preparation

General/New

Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. To have better finish rubbed down surface using suitable abrasive and dust off. If after thorough preparation surface remain powdery, or suffer from alkali attack, for best effect seal with 1 coat of Smart Green Sealer 850.

Previously Painted Surface

Remove all loose, defective and unstable paint film or powdery residues by thorough brushing and scraping. Make good minor defects and cracks with suitable grade filler.

Painting Guide

Surface Condition	Sealer 1 coated	Finish (2 coats)
Powdery Surface	<ul style="list-style-type: none"> • Smart Eco Sealer • Smart Wall Sealer 800 • Smart Green Sealer 850 • Smart Wall Sealer 900 • Smart Wall Sealer 400S 	Smart Eco Wash
Alkali/ New Surface	<ul style="list-style-type: none"> • Smart Eco Sealer • Smart Wall Sealer 800 • Smart Green Sealer 850 • Smart Wall Sealer 900 • Smart Wall Sealer 400S 	Smart Eco Wash