



Smart Solvent Base Roadline Paint

SPRLS
5 Litre



Description

Smart Solvent Base Roadline Paint is a modified alkyd solvent based air drying paint for road marking like center lines, edge line, car parking lines etc. It is fast drying with excellent abrasion resistance and self cleaning properties and has excellent resistance against bleeding through of bitumen.

Usage

For marking of road centerlines, edge lines, car park, pedestrian crossing and etc.

Composition

Pigment	:	Light fast pigment and mineral extenders
Binder	:	modified alkyd
Volume Solid	:	50%
Diluent	:	Aromatic hydrocarbon

Properties

Finishing	:	Low sheen
Colour	:	White, yellow and black
Theoretical Coverage	:	9m ² /Litre
Drying Time	:	* Touch dry – 5 – 10 min. * Hard dry – 20 – 30 min. *Dependent on temperature and humidity.
Recoating Interval	:	30 min.

Application Method

Brush	:	For normal use, thinning is usually not necessary.
Roller	:	For normal use, thinning is usually not necessary.
Conventional Air Spray	:	Thin with 10 -20% by volume with white spirit and adjust to requirement.
Airless Spray	:	Thinning is usually not necessary.

Surface Preparation

General/ New Surface

Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease and wax.

Previously Painted

Remove all loose, defective and unstable paint film or powdery residues by thoroughly brushing and scraping.

Composition / Information on Ingredients

Component	% by wt
Solvent Blend	10%
Alkyd Resin Blend	< 20%
Pigment	10 – 13%
Filler	45 - 50%

Company Identification

Manufacturer : Smart Paint Manufacturing Sdn. Bhd.
 No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,
 81800 Ulu Tiram, Johor, Malaysia
 Telephone No. : +607-863 9855 (Hunting Line) Fax No. : +607-861 5055
 Email : info@smart-paints.com