



Smart Roof Max

SPRM
5 Litres



Description

Smart Roof Max is a premium quality, highly durable, 100% acrylic based emulsion paint. It is specially formulated for the tropic roofing with excellent weathering properties, fungus and algae resistance. Highly recommend for old and new roof such as unglazed roof tiles, cement roof tiles and cement fibre roofing sheet. Smart Roof Max is Environment Friendly, non – lead and non – mercury. Incorporated with excellent light fast pigment with high mould and alkali resistance. This product is formulated to provide excellent gloss and low dirt retention.

Usage

For decoration and protection of roof tiles, block water seepage on old roof – tiles. Can also be painted on exterior cement and cement fibre structure. Roof Max excellent light fast pigment with high mould and alkali resistant formulation will provide a durable long lasting aesthetic finish.

Composition

| | | |
|--------------|---|--|
| Pigment | : | Lightfast Non – Lead Pigments and Mineral Extenders. |
| Binder | : | 100% Full Acrylic Emulsion. |
| Volume Solid | : | White 40% (Nominal) |
| Diluent | : | Water |

Properties

| | | |
|----------------------|---|--|
| Finishing | : | Smooth Sheen Finish. |
| Colour | : | Range of colours. Please refer Smart Roof Max Colour Card. |
| Theoretical Coverage | : | 11 – 12 m ² /Litre |
| Drying Time | : | Touch dry – 30 minutes. Hard dry – 3 Hours *Dependent on temperature and humidity. |
| Recoating Interval | : | Minimum 4 hours. |

Application Method

| | | |
|------------------------|---|--|
| Brush | : | For normal use thinning is not necessary. |
| Roller | : | For normal use thinning is not usually necessary. Can be thin 5% by volume with water to assist application. |
| Conventional Air Spray | : | Thin with 10% by volume with water and adjust to requirement. |
| Airless Spray | : | Thinning is not usually necessary. Can be thin 5% volume with water to assist application. |

Surface Preparation

General / New

Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. To have better finish rubbed down surface using suitable abrasive and dust off.

Previously painted

Remove all loose, defective and unstable paint film or powdery residues by thorough brush and scraping. High pressure water jet is highly recommended. Treat areas effected by mould, lichens, algae and moss with fungi wash. Make good minor defects and cracks with suitable filler.

Painting Guide

Finish (2-3 coats)

Smart Roof Max

Company Identification

Manufacturer : Smart Paint Manufacturing Sdn. Bhd.
 No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,
 81800 Ulu Tiram, Johor, Malaysia
 Telephone No. : +607-863 9855 (Hunting Line) Fax No. : +607-861 5055
 Email : info@smart-paints.com