



SILK GLO+

WASHABLE INTERIOR MID SHEEN WALL FINISH



TOPLUS

- LOW ODOUR
- LOW VOC
- EXCELLENT SCRUB RESISTANT
- WASHABLE AND CLEANABLE
- LUXURY SHEEN FINISH



SILK GLO+

WASHABLE INTERIOR MID SHEEN WALL FINISH

- LOW ODOUR
- LOW VOC
- EXCELLENT SCRUB RESISTANT
- WASHABLE AND CLEANABLE
- LUXURY SHEEN FINISH



TOPLUS SILK GLO+

TOPLUS SILK GLO+ is a specially formulated low VOC emulsion paint that provides a healthy living environment for the family. It provides a mid sheen wall finish that is able to enhance the indoor surface with luxurious feel while protecting the wall at the same time. The paint film is highly durable and washable which is suitable for interior wall and ceiling.

TOPLUS SILK GLO+

TOPLUS SILK GLO+ adalah cat emulsi dinding yang dirumus khas dengan sebatian organik yang kurang meruap yang dapat memberikan tempat penginapan yang mesra alam. Ia menyediakan cat kemas dinding yang berkilat dan mewah serta dapat melindunginya. Selain dari itu, ia juga memberi permukaan yang tahan lasak dan boleh dicuci. Rumusan ini sangat sesuai untuk dinding dalaman dan permukaan siling.

TOPLUS SILK GLO+

TOPLUS SILK GLO+ is specially formulated low VOC emulsion paint that provides a healthy living environment for the family. It provides a mid sheen wall finish that is able to enhance the indoor surface with luxurious feel while protecting the wall at the same time. The paint film is highly durable and washable which is suitable for interior wall and ceiling.

表面处理

确保表面干净及彻底干透，绝无松散的污垢，油脂或蜡迹。同时，也必须把已损坏的表面用 Putty Filla 修补好。欲取得最佳效果，请先涂上一层 Toplus Eco Sealer 5400，然后再涂上两层 TOPLUS SILK GLO+。

Penyediaan Permukaan

Pastikan permukaan yang hendak dicat bersih, dinding kering sepenuhnya dan bebas daripada segala bahan cat yang menyempah, kotoran, minyak atau lilin. Membaiki permukaan yang rosak atau retakan halus dengan Putty Filla sebelum menyapu cat. Untuk hasil yang cemerlang, sapu satu lapisan Toplus Eco Sealer 5400 diikuti dengan 2 lapisan TOPLUS SILK GLO+ . Biarkan 1-2 jam masa pengeringan diantara lapisan cat.

Surface Preparation

Ensure wall surface to be painted on is clean, thoroughly dry and free from all defects or poor adhering material like dirt, grease and wax. Repair surface defects or hairline crack by using Putty Filla before painting. For best result, apply 1 coat of Toplus Eco Sealer 5400 and followed by 2 coats of TOPLUS SILK GLO+ about 1-2 hours drying between coats.

配方资料

手触干度：视气温和湿度而定
复涂层漆：相隔一至两个小时
复涂面积：每公升十至十二平方公尺
层数：两层

Data Penggunaan

Kering Sentuh : Bergantung pada suhu kelembapan
Ulang Cat : 1-2 jam
Liputan : 10m - 12m² per/liter
Bilangan Lapisan : 2 lapisan

Application Data

Touch Dry : Dependent on temperature and humidity
Recoat : 1-2 hours
Coverage : 10m - 12m² per/litre
No. of Coats : 2 coats

用法

髹扫工具：使用前需彻底搅匀。可用漆扫、油漆滚筒涂扫或喷射。
调稀：通常不必调稀。如果需要调稀，用不超过10%的清水。
清理：髹漆工作完成后，即刻用清水洗净用具。

Cara Penggunaan

Cara Menggunakan : Kacau dengan sekata sebelum guna. Cat ini boleh disapu dengan menggunakan berus, penggelek atau penyembur.
Pencaliran : Untuk kegunaan biasa, pencaliran biasanya tidak perlu. Jika perlu, cairkan dengan maksimum 10% air.
Pencucian : Cuci semua peralatan dengan air sebaik sahaja selesai kerja.

Direction For Use

Application : Stir well before use. Application can be carried out by using brush, roller or by spraying.
Thinning : Use directly or dilute with a maximum of 10% water.
Cleaning Up : Clean all equipment with clean water immediately after use.



WATER BASE



INTERIOR



ROLL ON



BRUSH ON



SPRAY ON



1-2 HOURS RECOAT

SMART PAINT MANUFACTURING SDN BHD (1031014-A)
No. 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,
81800 Ulu Tiram, Johor, Malaysia.
email : info@smart-paints.com smart-paints.com



BUATAN MALAYSIA

INTERIOR PAINT



- LOW ODOUR
- LOW VOC
- EXCELLENT SCRUB RESISTANT
- WASHABLE AND CLEANABLE
- LUXURY SHEEN FINISH

