



## Smart Glo

SPSG  
1, 5 & 20 Litre



### Description

**Smart Glo** is a general purpose solvent based enamel gloss paint. Suitable for use on all types of wood and metal surfaces. Recommended for use where economy is important. For longer lasting durability on exposed surfaces, Smart High Gloss is recommended.

### Usage

For decoration and protection of all types of interior and exterior wood and metal surfaces.

### Composition

Pigment	:	Lightfast non-lead pigments and mineral extenders
Binder	:	Modified hydrocarbon resin.
Volume Solid	:	White 54% (nominal), others colours will vary.
Diluent	:	White Spirit

### Properties

Finishing	:	Gloss finish
Colour	:	Refer to color card.
Theoretical Coverage	:	9 - 11m <sup>2</sup> / Litre (actual coverage dependent on substrate condition.)
Drying Time	:	Touch dry – 1 Hours. Hard dry – 4 Hours *Dependent on temperature and humidity.
Recoating Interval	:	3 to 4 hours.

### Application Method

Brush	:	For normal use thinning is not usually necessary.
Roller	:	For normal use thinning is not usually necessary.
Conventional Air Spray	:	Thin with max 10 – 20 % by volume with white spirit.
Airless Spray	:	Ready for use. Thinning is not usually necessary.

### Surface Preparation

Surface	Preparation
Wood	Wood must be dry and free from grease, dirt, and other contaminants, smoothen surface with suitable grade sand paper and dust off before application of undercoat and paints.
Metal	Surface must be dry and free from grease, dirt and other contaminants. Steel surfaces should be sanded or wire-brushed to remove mill scales and rust.

Previously painted	Remove all loose, defective and unstable paint film. Rusted and defective areas should be sanded and feather edged and spot primed with red oxide primer or zinc chromate primer before applying subsequent coatings.
--------------------	---

### Painting Guide

Surface	Primer	Sealer (1 coat)	Finish (1 - 3 coats)
Wood	Aluminum Wood Primer	Undercoat	Smart Glo
Metal	Red oxide primer/ zinc chromate/ phosphate Primer	Undercoat	Smart Glo
Galvanized & Aluminum	Etch Primer	Undercoat	Smart Glo

### Company Identification

Manufacturer : Smart Paint Manufacturing Sdn. Bhd.  
 No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,  
 81800 Ulu Tiram, Johor, Malaysia  
 Telephone No. : +607-863 9855 (Hunting Line) Fax No. : +607-861 5055  
 Email : info@smart-paints.com