



Toplus Emulsion Paint

TP6

7 Litres & 18 Litres

Description

Toplus Emulsion Paint is an economical decorative finish. It is suitable to be applied on ceiling, normal interior masonry surfaces and soft wall boards. This product is specially formulated with styrene acrylic binder. It is highly recommended for use in housing scheme where economy is priority.

Usage

For decoration of wall, ceiling, plaster, brickworks, cement board, hard and soft board..

Composition

Pigment	:	Titanium dioxide and/or mineral extenders
Binder	:	Styrene acrylic
Volume Solid	:	40%
Diluent	:	Water

Properties

Finishing	:	Classic matt finish
Colour	:	White
Theoretical Coverage	:	12 – 13 m ² /Litre (actual coverage dependent on substrate condition.)
Drying Time	:	* Touch dry – 15 to 30 minutes. * Hard dry – 1 hour. *Dependent on temperature and humidity.
Recoating Interval	:	1 to 2 hours.

Application Method

Brush	:	Thin with 5 - 10% by volume with water.
Roller	:	Thin with 5 - 10% by volume with water.
Conventional Air Spray	:	Thin with 10 – 20% by volume with water.
Airless Spray	:	Thin with 10 – 20% by volume with water.

Surface Preparation

- Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease and wax. (To have a better finish, rub down surface using suitable abrasive and dust off.)
- If after thorough preparation surface remains powdery, for best effect seal with 1 coat of Wall Sealer. If the surface suffers from alkali attack, it is best recommended to seal with 1 coat of Smart Green Sealer 850.

Painting Guide

Surface Condition	Sealer (1 coat)	Finish (1 - 2 coats)
Powdery Surface	<ul style="list-style-type: none"> • Smart High Performance Sealer 900 (Solvent Base) • Smart Green Sealer 850 • Smart Wall Sealer 800 • Smart GP Wall Sealer 400 	Toplus Emulsion Paint
Alkali/ New Surface	<ul style="list-style-type: none"> • Wall Sealer 850 	Toplus Emulsion Paint

Company Identification

Manufacturer : Smart Paint Manufacturing Sdn. Bhd.
 No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,
 81800 Ulu Tiram, Johor, Malaysia
 Telephone No. : +607-863 9855 (Hunting Line) Fax No. : +607-861 5055
 Email : info@smart-paints.com