



## Toplus Silk Glo

TPSG  
5 Litre



### Description

**Toplus Silk Glo** is an eco and health friendly interior paint specially formulated for easy cleaning. This low odour, low VOC formula provides a tough and extremely smooth surface for easy cleaning. Stains can be easily wiped off, so the mid sheen finish walls are always clean and easy to maintain.

**Note :** Volatile organic compound (VOC) are air borne chemicals harmful to health and the environment.

### Usage

For decoration and protection of wall, ceiling, plaster, brickwork and cement board for a Smooth and Elegant Classic mid sheen finish.

### Composition

Pigment	:	Lightfast non-lead pigments and mineral extenders
Binder	:	Vinyl Acetate - Ethylene emulsion.
Volume Solid	:	White 45% (Nominal), other colours will vary.
Diluent	:	Water

### Properties

Finishing	:	Smooth Elegant Classic Mid Sheen Finish.
Colour	:	Refer to color card.
Theoretical Coverage	:	10 - 13m <sup>2</sup> / Litre (actual coverage dependent on substrate condition.)
Drying Time	:	*Touch dry – 15 minutes *Dependent on temperature and humidity.
Recoating Interval	:	1 to 2 hours.

### Application Method

Brush	:	For normal use thinning is not usually necessary.
Roller	:	For normal use thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application.
Conventional Air Spray	:	Thin with 10 – 20% by volume with water and adjust to requirement.
Airless Spray	:	Thinning is not usually necessary. Can be thin 5 – 10% volume with water to assist application.

## Surface Preparation

### General/New

Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. To have better finish rubbed down surface using suitable abrasive and dust off. If after thorough preparation surface remain powdery, or suffer from alkali attack, for best effect seal with 1 coat of Smart Green Sealer 850.

### Previously Painted Surface

Remove all loose, defective and unstable paint film or powdery residues by thorough brushing and scraping. Make good minor defects and cracks with suitable grade filler.

## Painting Guide

Surface	Primer (1 coat)	Finish (1 - 3 coats)
Powdery Surface	Smart GP Wall Sealer 400 Smart Wall Sealer 800 Smart Green Sealer 850 Smart Wall Sealer 900	Toplus Silk Glo
Alkali/ New Surface	Smart Green Sealer 850 Smart Wall Sealer 800 Smart Wall Sealer 900	Toplus Silk Glo

## Company Identification

Manufacturer : Smart Paint Manufacturing Sdn. Bhd.  
No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,  
81800 Ulu Tiram, Johor, Malaysia

Telephone No. : +607-863 9855 (Hunting) Fax No. : +607-861 5055  
Email : info@smart-paints.com