

# **Toplus Eco Sealer 5400** Sealer Paint for Masonry wall

# 5 Litres & 18 Litres

Version No. : 3.1.6

Issue Date: 17/02/2021 Safety Data Sheet according to CLASS requirement



oduct Identifier				
Product Name	Toplus Eco Sealer 5400			
Product Code	TPES-5400			
Chemical Name	Not Applicable			
Chemical Formula	Not Applicable			
Other means of Identification Sealer Paint for Masonry wall				
CAS Number	Not Applicable			
elevant use of the chemical and restriction				
	Use according to manufacturer's directions			
Relevant identified uses				
	SMART PAINT MANUFACTURING SDN BHD (1031014-A)			
etails of manufacturer / importer				
etails of manufacturer / importer Registered Company Name	SMART PAINT MANUFACTURING SDN BHD (1031014-A)			
etails of manufacturer / importer Registered Company Name Address	SMART PAINT MANUFACTURING SDN BHD (1031014-A) No. 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang, 81800 Ulu Tiram, Johor, Malaysia.			
etails of manufacturer / importer Registered Company Name Address Telephone	SMART PAINT MANUFACTURING SDN BHD (1031014-A) No. 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang, 81800 Ulu Tiram, Johor, Malaysia. +607-863 9855			
etails of manufacturer / importer Registered Company Name Address Telephone Fax	SMART PAINT MANUFACTURING SDN BHD (1031014-A) No. 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang, 81800 Ulu Tiram, Johor, Malaysia. +607-863 9855 +607-861 5055			
etails of manufacturer / importer Registered Company Name Address Telephone Fax Email	SMART PAINT MANUFACTURING SDN BHD (1031014-A) No. 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang, 81800 Ulu Tiram, Johor, Malaysia. +607-863 9855 +607-861 5055 info@smart-paints.com			
etails of manufacturer / importer Registered Company Name Address Telephone Fax Email Web	SMART PAINT MANUFACTURING SDN BHD (1031014-A) No. 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang, 81800 Ulu Tiram, Johor, Malaysia. +607-863 9855 +607-861 5055 info@smart-paints.com			
etails of manufacturer / importer Registered Company Name Address Telephone Fax Email Web	SMART PAINT MANUFACTURING SDN BHD (1031014-A) No. 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang, 81800 Ulu Tiram, Johor, Malaysia. +607-863 9855 +607-861 5055 info@smart-paints.com .http://www.smart-paints.com			

Classification of the substances or mixture	
GHS Classification	Physical Hazard - Not Classified
	Health Hazard
	Acute Toxicity Oral - Category 4
	Acute Toxicity Dermal - Category 4
	Environment Hazard
	Hazardous To The Aquatic Environment – Chronic Hazard - Category 3
Label elements	
GHS label elements	
Signal word	Warning
Hazard statement(s)	
H302	Harmful if swallowed
H312	Harmful if in contact with skin
H412	Harmful to aquatic life with long lasting effects.
Precautionary statement(s) Prevention	
P264	Wash affected hand and skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection / face protection.
1	

SECTION 2 HAZARDS IDENTIFICATION Precautionary statement(s) Response					
P330 RINSE mouth.					
P302+P352 IF ON SKIN : Wash with plenty of soap and water.					
P363 Wash contaminated clothing before reuse.					
Precautionary statement(s) Disposal					
P501	Dispose of content/ container to appropriate waste site or reclaimer in accordance with local or national regulations.				

CAS number	% [weight]	Name
-	45-50	Polymeric dispersion
13463-67-7	4-5	White Pigment
471-34-1	1-24	Calcium carbonate
55965-84-9	0.4	5-chloro-2-methyl-2H-isothiazol-3-one
000124-68-5	0.15-0.18	Alkanolamine
-	Balance	Substances determined to be non-hazardous

Description of first aid measure	
Eye contact	• Spashes in the eye must be washed out immediately with clean water for several minutes. Seek for medical attention.
Skin contact	• The skin should be washed with water before the emulsion dries, contaminated clothing must be removed to avoid discomfort from adhering paint. Some dried paint films that cannot be washed off the dried paint can be removed with skin cleanser. SOLVENTS MUST NOT BE USED.
Inhalation	<ul> <li>Discomfort due to the vapours of the residual monomer etc is unlikely to occur, but can easily be relieved by breathing fresh air.</li> </ul>

## SECTION 5 FIREFIGHTING MEASURES

# Suitable Fire Extinguishing Media :

The emulsion will not burn until water has evaporated for residual solid : Use water spray, carbon dioxide, dry chemical, alcohol-type or universal-type foams applied by manufacturers recommended techniques.

# Special Protective Actions For Fire Fighters:

No special fire fighting arrangements are necessary.

#### Specific Hazards Arising From The Chemical :

Non combustible.

Not considered a significant fire risk, however containers may burn.

## SECTION 6 ACCIDENTAL RELEASE MEASURES

# Personal Precautions, Protective Equipment And Emergency Procedure

Eye /skin protection : Where there is potential for eye contact, wear chemical goggles and have eye flushing equipment immediately available. Wear appropriate protective clothing and chemical resistant gloves to prevent skin contact. Wear a face shield and chemical resistant clothing such as rubber apron when splashing is likely. **Respiratory Protection :** Not required.

Ventilation : General room ventilation is expected to be satisfactory.

#### Environment Precaution

Although leakages/ spillages present little hazards, in the interests of preventing slippery or dangerous surfaces, they should be dealt with as soon as possible. Major spills should be collected for disposal. Minor spills may be flushed to a sewer if local regulations permit.

#### Methods And Materials For Containments And Clean Up

Contain spills immediately with inert materials( eg: sand, earth). Transfer liquids and solid material to separate suitable containers for recovery or disposal

# SECTION 7 HANDLING AND STORAGE

Precautions For Safe Handling Avoid smoking and use of open fire. Avoid breathing vapours.

Condition For Safe Storage ,including Any Incompatibilities Store in tightly closed original container in well-ventilated area. Avoid expose to direct sunlight.

# SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

# Control Parameters/ Occupational Limits

	ACGIH TLV-TWA		OSHA PEL-TWA		
Ingredient/Bahan	ppm	mg/m3	ppm	mg/m3	
Polymeric dispersion	-	-	-	-	
White Pigment	-	10	-	-	
Calcium carbonate	-	-	-	15	
5-chloro-2-methyl-2H-isothiazol-3-one	-	-	-	-	
Alkanolamine	-	-	-	-	

## APPROPRIATE ENGINEERING CONTROL MEASURES

If user operations generate dust, fumes, gas, vapours or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emission from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### PERSONAL PROTECTION

Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended : Full mask with type Cartridge filter.

#### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products I a risk assessment indicates this is necessary. After contamination with product change the gloves immediately and dispose of them according to relevant national and local regulations.

Eve protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Recommended : Safety glasses with side-shields.

#### Skin/ Body Protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Recommended : Wear protective clothing.

Appearance / colour	Liquid /White
Odour	Not Applicable
Solid	53.0%
Specific Gravity (@ 25°C)	1.24
Viscosity (Ku)	90.0 - 100.0
*Boiling Point	Not applicable
*Melting Point	Not applicable
*Vapour Pressure (@ 20°C)	Not applicable
Vapour Density (101.3 kPA / air=1)	Not applicable
Evaporation Rate (n - Butyl Ether=1)	Not applicable
Solubility	Soluble in water

# SECTION 10 STABILITY AND REACTIVITY

### REACTIVITY

No dangerous reaction known under condition of normal use.

#### CHEMICAL STABILITY

Stable under normal temperature conditions and recommended use.

#### POSSIBILTY OF HAZARDOUS REACTION

Under normal conditions of storage and use, hazardous reaction will not occur.

#### CONDITIONS TO AVOID

Heat, flame , sparks. Nitric acid, sulfuric acid, strong oxidizing agents. Electrostatic accumulation hazard? If Yes, use proper grounding procedure.

#### HAZARDOUS DECOMPOSITION PRODUCTS

Under normal conditions of storage and use, hazardous decompositions products should not be produced.

Oral	Dermal	Inh (Gas)	Inh (Vapor)	Inh (Dust/mis
	sure) : Not classified : Not classified : Not classified : Not data : Not Classified : Not Classified : Not data : Not Classified	: Not Classified : No Data : Not Classified : Not Classified : Not Classified : Not Classified : Not Classified re) : Not Classified : Not Classified	: Not Classified : No Data : Not Classified : Not Classified : Not Classified : Not Classified : Not Classified re) : Not Classified : Not Classified	: Not Classified : No Data : Not Classified : Not classified

		INFORMATION
SECTION 12	ECOLOGICAL	INFORMATION

# Ecotoxicity

No data available.

#### Persistence And Degradability No information available

# **Bioaccumulative Potential**

Accumulation in aquatic organisms is unlikely.

# Mobility In Soil

Potential for mobility in soil.

#### Other Adverse Effects

Do not allow product to reach ground water, water course or sewage system.

Ingredient	Fish 96 hour, LC50	Crustacea 48 hour, EC50	Inh (Gas)LC50
5-chloro-2-methyl-2H-isothiazol-3-one	0.19mg/l	0.16mg/l	0.003 mg/l
Alkanolamine	11800mg/l	609.88mg/l	216-512 mg/l

# SECTION 13 DISPOSAL INFORMATION

#### Waste Disposal :

Product Disposal:

Recover or recycle if possible. Otherwise dispose in accordance with all applicable with all applicable national environment laws and regulations.

This product when dispose of in its unused and uncontaminated state should be treated as a hazardous waste.

#### Container Disposal :

Drain container thoroughly. Rinse three times with suitable solvent. Treat rinsing as for product disposal. After draining, vent in a safe place away from sparks and fire. Send drum recoverer or metal reclaimer. Residue may cause an explosion hazard. Do not pincture, cut or weld uncleaned drums. Keep container labelled until cleaned and then remove or deface labels.

Transport to be in accordance with ADR/RID for road/rail, IMDG for sea and IATA for air.

# LAND TRANSPORT

Classified as None Dangerous Goods by the criteria of the European Agreement concerning the international carriage of Dangerous Goods (ADR) by Road & Regulations concerning the international carriage of Dangerous Goods (RID) by Rail.

UN Number : N/R Class : N/R Packaging Group : N/R

# SEA TRANSPORT

Classified as None Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG) for the transport of Sea.

UN Number : N/R Class : N/R Packaging Group : N/R Marine Pollutant : No SEA (Annex II of MARPOL 73/78 and the IBC Code) : Not Applicable

# AIR TRANSPORT

Classified as None Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for the transport by Air.

UN Number : N/R Class : N/R Packaging Group: N/R

## SECTION 15 REGULATORY INFORMATION

Applicable national regulations :

a) OHSA 1994 and relevant regulation

b) Factories and Machinery Act 1967 and relevant regulations

c) Environment Quality Act 1967 and regulations.

d) Pesticide Act 1974 and regulations

- e) Occupational Safety and Health (Classification, Labelling And Safety Data Sheet of Hazardous Chemicals) Reg 2013
- f) Industry Code Of Practice (On Chemicals Classification And Hazard Communication

# SECTION 16 OTHER INFORMATION

Date of preparation : 15-07-2013Date of revision: 05-02-2021Version: 02

#### ABBREVIATION

- ACGIH American Conference of Governmental Industrial Hygienists
- TLV Threshold limit value
- TWA Time-Weighted Average
- OSHA Occupational Safety and Health Administration
- PEL Permissible Exposure Limit
- LD50 Lethal Dose
- LC50 Median Lethal concentration
- IACR International Agency for Research in Cancer
- CAS Registry Numbers Chemical Abstracts Service Registry Numbers
- ICOP Industry Code Of Practice on Chemical Classification and Health approved by Minister under section 37 of the Act
- C Ceiling Limit
- CEIL Ceiling Limit airborne concentration
- STEL Short Term Exposure Limit
- DNA Data Not Available
- N/R Not Regulated

Disclaimer

All information appearing here in is based on our present state of our knowledge. However the information in this SDS may not be valid for such material used in combination with any other materials or in any process. No representation, warranty or guarantee is made as to its accuracy, reliability or completeness. We do not accept liability for any loss or damage that may occur from the use of this information.