



WEATHER PLUS



FULL ACRYLIC EXTERIOR WALL FINISH

TOPLUS

- Excellent Fungus And Algae Resistant
- Excellent Durability And Color Fastness
- Dirt Resistant
- UV Resistant



WEATHER PLUS



FULL ACRYLIC EXTERIOR WALL FINISH



TOPLUS WEATHER PLUS

TOPLUS WEATHER PLUS is a specially formulated acrylic paint for tropical weather. It provides excellent durability and color fastness against harsh weather conditions. The product is resistant to mold, algae, and dirt, ensuring a long-lasting finish. It is also resistant to UV rays, preventing fading and discoloration over time.

TOPLUS WEATHER PLUS

TOPLUS WEATHER PLUS dirumuskan khas untuk cuaca tropika. TOPLUS WEATHER PLUS berasaskan 100% akrilik dan ia dapat menyediakan pertahanan yang kuat terhadap cuaca yang panas terik. Selain itu, ia adalah kemasangan dinding luar yang berprestasi tinggi dan dapat memberi sekurang-kurangnya 6 tahun perlindungan daripada pertumbuhan kulat dan rumput air. TOPLUS WEATHER PLUS tahan kepada panas terik matahari dan hujan lebat. Ia juga memberi perlindungan yang kuat terhadap kotoran, kulat dan serangan alkali.

TOPLUS WEATHER PLUS

TOPLUS WEATHER PLUS is specially designed for tropical weather. TOPLUS WEATHER PLUS is formulated with 100% acrylic, which provides a tough finish and high level of durability against harsh weather. Besides, it is a high performance exterior wall finish specially formulated to provide at least 6 years of protection against unsightly fungi and algae growth. It can also withstand the scorching sun and torrential rain. TOPLUS WEATHER PLUS breakthrough formula provides a tougher resistance against dirt, fungus, flaking and alkali attack.

表面处理

确保表面干净，使用硬刷及用水冲洗或以喷射法除掉松脱的漆片，用除霉波处理霉菌、真菌和苔藓侵袭的表面，待干后才上漆。使用适合的漆泥修补小缺陷。为了取得最佳效果，请先涂上一层 Solvent Based Sealer 或 TOPLUS ECO-SEALER 5400 然后再涂上两层 TOPLUS WEATHER PLUS。注意：别在潮湿的天气涂刷 TOPLUS WEATHER PLUS。

Penyediaan Permukaan

Pastikan permukaan yang hendak dicat bersih. Buang segala cat mengelupas atau sisa berserbuk dengan berus atau kikir dengan berus sabut keras dan air atau pancutan air yang mempunyai tekanan tinggi. Rawati bahagian yang terjerjas akibat kulat, liken, rumput air atau lumut. Biarkan kering sebelum mengecat. Baiki kerosakan kecil dengan filler luaran yang sesuai. Untuk hasil yang cemerlang, sapu satu lapisan Solvent Based Sealer atau TOPLUS ECO-SEALER 5400 diikuti dengan 2 lapisan TOPLUS WEATHER PLUS.

Surface Preparation

Ensure the surface to be painted is clean. Remove all loose paint or powdery residue by brushing or scraping with a stiff brush under running water or with a high pressure water jet. Treat areas affected by mould, lichen, algae or moss with fungicidal wash and allow them to dry before painting. Repair minor defects with a suitable exterior graded filler. For best results, apply 1 coat of Solvent Based Sealer or TOPLUS ECO-SEALER 5400 followed by 2 coats of TOPLUS WEATHER PLUS.

Perhatian: Jangan sapu kemasangan dinding luar dengan TOPLUS WEATHER PLUS dalam cuaca lembap.

Note: Do not apply TOPLUS WEATHER PLUS in damp weather.

施工资料

手触干度 : 视气温和湿度而定
 髹次层漆 : 相隔一至两个小时
 髹扫面积 : 每公升十一至十三平方米
 层数 : 两层

Data Penggunaan

Kering Sentuh : Bergantung kepada suhu dan kelembapan
 Ulang Cat : 1-2 jam
 Liputan : 11-13m²/ liter
 Bilangan Lapisan : 2 lapisan

Application Data

Touch Dry : Dependent on temperature and humidity
 Recoat : 1-2 hours
 Coverage : 11-13m²/ litre
 No. of Coats : 2 coats

用法

髹扫用具 : 使用前需彻底搅均，可用漆扫，滚轴涂刷或喷射。
 调稀 : 通常不必调稀。如果需要调稀，用不超过10%的清水。
 清理 : 髹漆工作完成后即刻用清水洗净用具。

Cara Penggunaan

Cara Menggunakan : Kacau sehingga sekata sebelum menggunakannya. Cat ini boleh disapu dengan berus, pengelek atau penyembur.
 Pencairan : Untuk kegunaan biasa, pencairan lazimnya tidak perlu. Jika perlu, cairkan dengan maksimum 10% air.
 Pencucian : Cuci perkakas dengan air bersih sebaik sahaja selesai kerja.

Direction For Use

Application : Stir well before use. Application can be carried out by using brush, roller or spraying.
 Thinning : Use directly or dilute with a maximum of 10% water.
 Cleaning Up : Clean all equipment with clean water immediately after use.



WATER BASE



EXTERIOR



ROLL ON



BRUSH ON



SPRAY ON



ALGAE & FUNGUS RESISTANT



1-2 HOURS RECOAT

SMART PAINT MANUFACTURING SDN BHD (1031014-A)

No. 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang, 81800 Ulu Tiram, Johor, Malaysia.

email : info@smart-paints.com smart-paints.com



BUATAN MALAYSIA

- Excellent Fungus And Algae Resistant
- Excellent Durability And Color Fastness
- Dirt Resistant
- UV Resistant

EXTERIOR PAINT



- EXCELLENT FUNGUS AND ALGAE RESISTANT
- EXCELLENT DURABILITY AND COLOR FASTNESS
- DIRT RESISTANT
- UV RESISTANT



Colour Scheme

