

## Toplus Weather Plus

TPWP  
5 & 18 Litre



### Description

**Toplus Weather Plus** is a premium quality, 100% full acrylic based emulsion paint. It is specially formulated for the tropics with excellent weathering properties, fungus and algae resistance. Toplus Weather Plus finishes have excellent alkali resistance, adhesion and durability. It is formulated to provide at least 5 years protection against fungus and algae growth with correct application.

### Usage

For decoration and protection of previously painted or new exterior walls for a long lasting aesthetic finish.

### Composition

Pigment	:	Lightfast Non – Lead Pigments and Mineral Extenders.
Binder	:	100% Full Acrylic Emulsion.
Volume Solid	:	White 40% ( Nominal), others colours will vary.
Diluent	:	Water

### Properties

Finishing	:	Smooth Matt Finish.
Colour	:	A wide range of colours. Please refer Toplus Weather Plus Colour Card.
Theoretical Coverage	:	11 – 13 m <sup>2</sup> /Litre
Drying Time	:	*Touch dry – 15 to 30 minutes. * Hard dry – 1 to 2 hour. *Dependent on temperature and humidity.
Recoating Interval	:	1 to 2 hours.

### Application Method

Brush	:	For normal use thinning is not usually necessary.
Roller	:	For normal use thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application.
Conventional Air Spray	:	Thin with 10 – 20% by volume with water and adjust to requirement.
Airless Spray	:	Thinning is not usually necessary. Can be thin 5 – 10% volume with water to assist application.

### Surface Preparation

Remove all loose, defective paint or powdery residues by wire brushing, scraping, or high pressure water jet. Treat any areas affected by fungus growth with fungicidal wash solution and left dry before painting. Repair cracks, uneven surfaces with putty or suitable fillers. Smoothen the putty areas with sandpaper. Make sure all surfaces are dry before painting. Avoid painting when the moisture content of the walls are still high. (Recommended painting specification requires the moisture content of the walls to be below 16% measured by Protimeter)

## Painting Guide

Surface	Primer (1 coat)	Finish (1 - 3 coats)
Powdery Surface	Smart Green Sealer 850 Smart Wall Sealer 800 Smart Wall Sealer 900	Toplus Weather Plus
Alkali/ New Surface	Smart Green Sealer 850 Smart Wall Sealer 800 Smart Wall Sealer 900	Toplus Weather Plus

## Company Identification

Manufacturer : Smart Paint Manufacturing Sdn. Bhd.  
 No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,  
 81800 Ulu Tiram, Johor, Malaysia  
 Telephone No. : +607-863 9855 (Hunting) Fax No. : +607-861 5055  
 Email : info@smart-paints.com