

## Smart Woodstain

SPWOOD  
1, 5 & 20 Litre



### Description

**Smart Woodstain** is a specially formulated Urethane Alkyd base high gloss enamel finish for protection of wooden surface. It has good water resistance, UV protection, anti fungus properties. It is fast drying and easily recoatable.

### Usage

Suitable for use in both interior and exterior where maintaining the texture of wood is desired.

### Composition

Pigment	:	Lightfast non-lead pigments and mineral extenders
Binder	:	Urethane alkyd base
Volume Solid	:	40 +/- 2%
Diluent	:	White Spirit

### Properties

Finishing	:	Gloss finish
Colour	:	Refer to color card.
Theoretical Coverage	:	10 - 12 m <sup>2</sup> /Litre (actual coverage dependent on substrate condition.)
Drying Time	:	* Touch dry – 30 minutes. * Hard dry – 3 - 4 hour. *Dependent on temperature and humidity.
Recoating Interval	:	3 to 4 hours.

### Application Method

Brush	:	For normal use thinning is not usually necessary.
Roller	:	For normal use thinning is not usually necessary.
Conventional Air Spray	:	Thin with max 10% by volume with white spirit.

### Surface Preparation

Surface	Preparation
New Wood	Surface generally must be clean, dry and free from oil, dirt, wax, grease or other contaminants. Recommend to test color on wood before decide the shade as final color shade depends on the type of wood applied. If gum is presence on surface, it must be clean by lacquer thinner. For recoating, the surface must be rub and clean.
Previously Painted Wood	Previously painted surface should be thoroughly rubbed down using suitable sandpaper and then dusted off.

## Painting Guide

Surface	Sealer (1 coat)	Finish (1 - 3 coats)
Wood	-	Smart Woodstain

## Company Identification

Manufacturer : Smart Paint Manufacturing Sdn. Bhd.  
 No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,  
 81800 Ulu Tiram, Johor, Malaysia  
 Telephone No. : +607-863 9855 (Hunting Line) Fax No. : +607-861 5055  
 Email : info@smart-paints.com