



Smart Cool Weather 8

SPTBCW

1L, 5L, 15L & 20L



Description

Smart Cool Weather 8 Paint is a premium, high-performance premium acrylic-based exterior emulsion specially designed to withstand harsh weather conditions. It delivers a smooth, elegant finish while offering excellent water resistance and strong adhesion for lasting protection. With advanced resistance to mold, mildew, and dirt, it keeps exterior surfaces looking clean and vibrant for longer. Perfect for exterior masonry surfaces including homes, buildings, and commercial projects, Cool Weather 8 Paint comes with an 8-year performance warranty.

Recommended uses

Exterior walls of concrete, plaster, cement render, brickwork, fibre cement board.

Composition

Pigment	:	Titanium Dioxide and Mineral Extenders.
Binder	:	Premium Acrylic Emulsion
Volume Solid	:	40%
Diluent	:	Water

Properties

Base	:	Bases & White
Finishing	:	Smooth Matt Finish.
Colour	:	Please refer to Smart Paint shade card and fan decks
Theoretical Coverage	:	11 – 13 m ² /Litre
Drying Time	:	Touch dry – 15 to 30 minutes. Hard dry – 1 to 2 hour.
		*Dependent on temperature and humidity.
Recoating Interval	:	1 to 2 hours.

Application Method

Brush	:	For normal use thinning is not necessary.
Roller	:	For normal use thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application.
Conventional Air Spray	:	Thin with 10 – 20% by volume with water and adjust to requirement.
Airless Spray	:	Thinning is not necessary. Can be thin 5 - 10% by volume with water to assist application.

Application Conditions

1. Surface temperature: 10°C - 40°C
2. Relative humidity: <85%
3. Avoid application during rain or extreme weather

Surface Preparation

- Remove all loose, defective paint or powdery residues by wire brushing, scraping, or high pressure water jet. Treat any areas affected by fungus growth with fungicidal wash solution and left dry before painting. Repair cracks, uneven surfaces with putty or suitable fillers. Smoothen the putty areas with sandpaper. Make sure all surfaces are dry before painting. Avoid painting when the moisture content of the walls are still high. (Recommended painting specification requires the moisture content of the walls to be below 16% measured by Protimeter)

Painting Guide

Surface Condition	Sealer (1 coat)	Finish (1 - 2 coats)
Powdery Surface	<ul style="list-style-type: none"> Smart Green Sealer 850 Smart Wall Sealer 900 	Smart Cool Weather 8
Alkali/ New Surface	<ul style="list-style-type: none"> Smart Green Sealer 850 	Smart Cool Weather 8

Storage and handling

Store in a cool, dry place away from direct sunlight, keep container tightly closed when not in use and stir thoroughly before use

Disclaimer

The information provided in this TDS is based on laboratory testing and practical experience. Actual performance may vary depending on application methods, surface condition and environmental factor. For the best results, follow the recommendation application guidelines.

Company Identification

Manufacturer : Smart Paint Manufacturing Sdn. Bhd.
 No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,
 81800 Ulu Tiram, Johor, Malaysia
 Telephone No. : +607-863 9855 (Hunting Line) Fax No. : +607-861 5055
 Email : info@smart-paints.com