



Smart Smartex Emulsion Paint

SP6STD

1 Litre, 7 Litres & 18 Litres



Description

Smart Smartex Emulsion Paint is an economical decorative wall finish with algae and fungus resistance. It is suitable for all normal interior and exterior masonry surfaces and soft wall boards. Smart Smartex Emulsion Paint is based on styrene acrylic binder which imparts high degree of washability and durability. Smart Smartex Emulsion Paint is specially formulated to be low VOC, low odour and easy application (using Smart Flow Technology). It is highly recommended for housing scheme and where economy is priority.

Usage

For decoration and protective of wall, ceiling, plaster, brickworks, cement board, hard and soft board.

Composition

Pigment	:	Lightfast Non – Lead Pigments and Mineral Extenders.
Binder	:	Styrene acrylic.
Volume Solid	:	43% (nominal), other colour will be vary.
Diluent	:	Water

Properties

Finishing	:	Classic matt finish
Colour	:	44 colours. Refer to Smart Smartex Emulsion Paint Colour Card.
Theoretical Coverage	:	10 – 13 m ² /Litre (actual coverage dependent on substrate condition.)
Drying Time	:	Touch dry – 15 to 30 minutes. Hard dry – 1 hour. *Dependent on temperature and humidity.
Recoating Interval	:	1 to 2 hours.

Application Method

Brush	:	Thin with 5 - 10% by volume with water.
Roller	:	Thin with 5 - 10% by volume with water.
Conventional Air Spray	:	Thin with 10 – 20% by volume with water.
Airless Spray	:	Thin with 10 – 20% by volume with water.

Surface Preparation

- Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease and wax. (To have a better finish, rub down surface using suitable abrasive and dust off.)
- If after thorough preparation surface remains powdery, for best effect seal with 1 coat of Smart GP Wall Sealer 400. If the surface suffers from alkali attack, it is best recommended to seal with 1 coat of Smart Wall Sealer 800.

Painting Guide

Surface Condition	Sealer (1 coat)	Finish (1 - 2 coats)
Powdery Surface	<ul style="list-style-type: none"> • Smart High Performance Sealer 900 (Solvent Base) • Smart Green Sealer 850 • Smart Eco Sealer • Smart Wall Sealer Super 5400 • Smart Wall Sealer 400S 	Smart Smartex Emulsion Paint
Alkali/ New Surface	<ul style="list-style-type: none"> • Smart High Performance Sealer 900 (Solvent Base) • Smart Green Sealer 850 • Smart Eco Sealer • Smart Wall Sealer Super 5400 • Smart Wall Sealer 400S 	Smart Smartex Emulsion Paint

Company Identification

Manufacturer : Smart Paint Manufacturing Sdn. Bhd.
 No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,
 81800 Ulu Tiram, Johor, Malaysia
 Telephone No. : +607-863 9855 (Hunting Line) Fax No. : +607-861 5055
 Email : info@smart-paints.com