



## Smart Eco-Sport Floor

SPTBES

5 Litres

### Description

**Smart Eco-Sport Floor** is an eco-friendly water-based paint designed for interior and exterior sport floor finishes. This product can be post added with silica sand and anti-slip polymer to enhance abrasive resistance.

Product features :

- Exterior & Interior Floor use
- Excellent Adhesion
- UV Resistant
- Excellent Water Resistant
- Abrasive Resistant & Mechanical Damage
- Fungus Resistant

### Usage

Flooring

### Composition

|              |   |  |
|--------------|---|--|
| Pigment      | : | Lightfast Non – Lead Pigments and Mineral Extenders. |
| Binder       | : | Pure Acrylic Solution                                |
| Volume Solid | : | 40%  |

### Properties

|                      |   |  |
|----------------------|---|--|
| Finishing            | : | Low Sheen  |
| Colour               | : | A wide range of colours. Please refer Smart Colour Card 68   |
| Theoretical Coverage | : | 3.45 m <sup>2</sup> per litre per coat based on 100 µm dry film thickness<br>1.73 m <sup>2</sup> per litre per coat based on 200 µm dry film thickness<br>Recommended No. of Coats: 2 coats (apply after using recommended primer) |
| Theoretical Coverage | : | Touch dry : minimum 30 minutes (Dependent on temperature and humidity)<br>Hard dry : minimum 1 hour (Dependent on temperature and humidity)  |
| Recoating Interval   | : | 2 hours minimum based on normal condition colours  |

### Application Method

|                        |   |   |
|------------------------|---|---|
| Brush                  | : | For normal use thinning is not necessary.   |
| Roller                 | : | For normal use thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application. |
| Conventional Air Spray | : | Thin with 10 – 20% by volume with water and adjust to requirement.  |
| Airless Spray          | : | Thinning is not usually necessary. Can be thin 5 – 10% volume with water to assist application.                   |

## Surface Preparation

The surface to be painted should be clean, dry and free from peeling, powdery and dusty residue, dirt, fungus and algae. For best result, apply 1 coat of Smart High Performance Sealer 900, Smart Green Sealer 850 or Epoxy Primer followed by 2 coats of Smart Eco-Sport Floor.

## Painting Guide

| Surface Condition                                      | Sealer (1 coat)   | Finish (1-2 coats)    | Optional Finish (1-2 coats)   |
|--|---|-----------------------|---|
| For Recoat Floor Surface with previous coating cleaned | <ul style="list-style-type: none"> <li>• Smart High Performance Sealer 900</li> <li>• Smart Green Sealer 850</li> <li>• Epoxy Primer</li> </ul> | Smart Eco-Sport Floor | <b>5L Smart Eco-Sport Floor</b><br>mix with <b>1kg Silica Sand</b><br>OR<br><b>250g Smart Anti-Slip Polymer</b> |
| New Cement Floor Surface                               | <ul style="list-style-type: none"> <li>• Smart High Performance Sealer 900</li> <li>• Smart Green Sealer 850</li> <li>• Epoxy Primer</li> </ul> | Smart Eco-Sport Floor | <b>5L Smart Eco-Sport Floor</b><br>mix with <b>1kg Silica Sand</b><br>OR<br><b>250g Smart Anti-Slip Polymer</b> |

## Company Identification

**Manufacturer** : Smart Paint Manufacturing Sdn. Bhd.  
No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,  
81800 Ulu Tiram, Johor, Malaysia  
**Telephone No.** : +607-863 9855 (Hunting Line) **Fax No. :** +607-861 5055  
**Email** : info@smart-paints.com