



## Smart Epoxy Tile Topcoat Clear (100% solid, solvent free)

SPETP-Clear

0.74KG (Part A) and 0.26 KG (Part B)



### Description

Smart Epoxy Tile Topcoat Clear is a two-pack system of epoxy primer barrier coating designed for use on ceramic tile & concrete floor surface which provide good adhesion to the substrate. It is suitable for use as tie coat between concrete substrate and colour flakes or to be use as tie coat between concrete substrate and solvent based topcoat such as Smart Epoxy BE4 or BE5 Finish.

### Usage

Flooring / Wall

### Composition

Pigment	:	Liquid / Clear
Binder	:	Epoxy resin.
Volume Solid	:	100%

### Properties

Finishing	:	Gloss finish
Colour	:	-
Theoretical Coverage	:	Recommended No. Of Coats : 1

Recommended Film Thickness Per Coat : 50µm

Theoretical Coverage At Recommended Film Thickness :  
6.25m<sup>2</sup>/L

Practical Coverage (20% Loss Factor) :  
5.0 m<sup>2</sup> /litre (for dry film thickness of 50 microns)

Drying Time	:	Dry to touch: 2 hours Dry to overcoat: 2 hours Curing time: 6-7 days
-------------	---	--

Pot Life	:	<b>20 min after mixing</b>
Mixing Ratio	:	Part A : 0.74kg + Part B : 0.26kg

### Application Method

Brush	:	No thinning required.
Roller	:	No thinning required.
Conventional Air Spray	:	-
Airless Spray	:	-

## Surface Preparation

Surfaces to be painted should be clean, dry and free from oil, grease and contaminants before painting. For previously painted surfaces, remove all unstable paint film, dust and foreign matter. Repair any surface defects, clean off and dry before using Smart Epoxy Tile Finish.

Recommended no. of coats: 1 coat

Recommended film thickness per coat: 50 microns for dry film; 165microns for wet film

## Company Identification

Manufacturer : Smart Paint Manufacturing Sdn. Bhd.  
No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,  
81800 Ulu Tiram, Johor, Malaysia

Telephone No. : +607-863 9855 (Hunting Line) Fax No. : +607-861 5055

Email : info@smart-paints.com