

Smart Elasto Hybrid (All-In-1)

SPTBELHY
5 Kg & 20 Kg



Description

SMART ELASTO HYBRID (ALL-IN-1) is a single component, ready-to-use, water-based acrylic polymer. The excellent water, alkali, and efflorescence resistance of this product, in combination with its exterior durability and its ability to adhere to a variety of substrates, allow it to be used in many applications. It can be used for RC gutters and planter boxes, floor slabs, deck, wood siding/fences, external wall, flat roof, metal roof and even concrete structures. It can also be applied as a sealing solution to seal cracks on joint walls, ceiling and roofing.

ELASTO HYBRID (ALL-IN-1) cures to form a tough and seamless waterproofing membrane with excellent adhesion to most substrates.

Advantage

- Able to bridge crack up to 2mm.
- Waterproof.
- User friendly. Highly recommended for DIY purpose.
- High rate of water vapour transmission which permits moisture pass through paint film, without causing any blistering, peeling or flaking.
- Prevention of ravages of acid rain, freeze-thaw, sunlight and etc.
- Can withstand low foot traffic.
- Non-toxic

Usage

- RC gutter and planter boxes.
- Floor slabs
- Deck.
- Terraces and balconies.
- Wood siding/ fencing wall.
- Flat roof.
- Metal roof.
- Concrete structure.

Composition

Pigment	:	Titanium dioxide, inorganic pigment.
Binder	:	Acrylic polymer
Volume Solid	:	40%
Diluent	:	Water

Properties

Finishing	:	Egg-shell-like finish
Colour	:	Refer to Smart Colour
Theoretical Coverage	:	8m ² /kg
Curing Time	:	12 Hours
Recoating Interval	:	8 hours.
Elongation	:	410.1%
Tensile Strength	:	4.8N/mm ² (Equivalent to 48.9kgf/cm ²)
Adhesion	:	0.95N/mm ²
QUV Accelerated Weathering	:	No cracking.

Application Instruction

The substrate must be clean and sound, free of dust and loose particles. Laitance, oil, grease, mould release agents or any foreign contaminants which may inhibit adhesion must be removed from concrete surfaces by using wire brush, scabblers or other means. Where moss, algae, or similar growths have occurred, treatment with suitable chemicals should be carried after the initial cleaning process followed by further washing.

Ensure the surface is dry, then coat with two layers of Smart Elasto HYBRID (ALL-IN-1). To obtain better weathering properties, it is recommended to paint with two layers of Smart Cool Weather.

Surface Preparation

Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease and wax.

Store Condition

Store in unopened and undamaged packaging in dry condition. Protect from direct sunlight.

Company Identification

Manufacturer	:	Smart Paint Manufacturing Sdn. Bhd. No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang, 81800 Ulu Tiram, Johor, Malaysia
Telephone No.	:	+607-863 9855 (Hunting Line) Fax No. : +607-861 5055
Email	:	info@smart-paints.com