

## Smartex WOW! Emulsion

SPTBWOW

1 Litre, 5 Litres & 18 Litres



### Description

**Smartex WOW! Emulsion Paint** is a specially formulated paint for interior masonry. It provides an attractive smooth matt finish on walls, asbestos, hard and soft boards. It provides higher opacity, durability and better washability as compared to normal economy emulsion paint.

### Usage

For decoration and protective of wall, ceiling, plaster, brickworks, cement board, hard and soft board.

### Composition

Pigment	:	Titanium dioxide and mineral extenders.
Binder	:	Styrene acrylic.
Volume Solid	:	52%
Diluent	:	Water

### Properties

Finishing	:	Matt finish
Colour	:	Refer to colourcard
Theoretical Coverage	:	10 – 13 m <sup>2</sup> /Litre (actual coverage dependent on substrate condition.)
Drying Time	:	Touch dry – 15 to 30 minutes.
	:	Hard dry – 1 hour.
		*Dependent on temperature and humidity.
Recoating Interval	:	1 to 2 hours.

### Application Method

Brush	:	Thin with 5 - 10% by volume with water.
Roller	:	Thin with 5 - 10% by volume with water.
Conventional Air Spray	:	Thin with 10 – 20% by volume with water.
Airless Spray	:	Thin with 10 – 20% by volume with water.

### Surface Preparation

- Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease and wax. (To have a better finish, rub down surface using suitable abrasive and dust off.)
- For best effect seal with 1 coat of Smart Wall Sealer 400S. If the surface suffers from alkali attack, it is best recommended to seal with 1 coat of Smart Green Sealer 850.

## Painting Guide

Surface Condition	Sealer (1 coat)	Finish (1 - 2 coats)
Powdery Surface	<ul style="list-style-type: none"> <li>• Smart High Performance Sealer 900 (Solvent Base)</li> </ul>	Smartex WOW! Emulsion
Alkali/ New Surface	<ul style="list-style-type: none"> <li>• Smart High Performance Sealer 900</li> <li>• Smart Green Sealer 850</li> </ul>	Smartex WOW! Emulsion