



# Smart Leakproof Master (Part A)

## 2 Pack High Solid Polyurethane Coating

### 0.5 Litre & 2.5 Litres

Version No. :

Issue Date: 05/06/2024

Safety Data Sheet according to CLASS requirement



SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING	
<b>Product Identifier</b>	
Product Name	Smart Leakproof Master
Product Code	SPLPM
Chemical Name	Not Applicable
Chemical Formula	Not Applicable
Other means of Identification	2 Pack High Solid Polyurethane Coating
CAS Number	Not Applicable
<b>Relevant use of the chemical and restriction</b>	
Relevant identified uses	Use according to manufacturer's directions
<b>Details of manufacturer / importer</b>	
Registered Company Name	SMART PAINT MANUFACTURING SDN BHD (1031014-A)
Address	No. 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang, 81800 Ulu Tiram, Johor, Malaysia.
Telephone	+607-863 9855
Fax	+607-861 5055
Email	info@smart-paints.com
Web	<a href="http://www.smart-paints.com">http://www.smart-paints.com</a>
<b>Emergency telephone number</b>	
Association / Organisation	Not Applicable
Emergency telephone number	Not Applicable
Other emergency telephone number	Not Applicable

SECTION 2 HAZARDS IDENTIFICATION	
<b>Classification of the substances or mixture</b>	
GHS Classification	Health Hazard Flammable liquids - Category 3 Skin Sensitization - Category 1
<b>Label elements</b>	
GHS label elements	
Signal word	Warning
<b>Hazard statement(s)</b>	
H226	Flammable liquid and vapour.
H317	May cause an allergic skin reaction.

Precautionary statement(s)	
<b>P210</b>	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
<b>P233</b>	Wear protective gloves/protective clothing/eye protection/face protection.
<b>P241</b>	Use explosion-proof electrical/ ventilating/lighting equipment.
<b>P242</b>	Obtain special instructions before use.
<b>P243</b>	Do not handle until all safety precautionary have been read and understood.
<b>P261</b>	Avoid breathing dust/fume/gas/mist/vapours/spray.
<b>P280</b>	Use personal protective equipment as required.
<b>P271</b>	Use only outdoors or in a well-ventilated area.
<b>P272</b>	Contaminated work clothing shall not be allowed out of the workplace.

SECTION 2 HAZARDS IDENTIFICATION	
<b>Precautionary statement(s) Response</b>	
<b>P302+P352</b>	IF ON SKIN : Wash with plenty of water and soap.
<b>P332+P313</b>	If skin irritation occurs : Get medical advice / attention
<b>P303+P361+P353</b>	IF ON SKIN (or hair) : Remove /take off immediately all contaminated clothing. Rinse skin with water/ shower.
<b>P370+P378</b>	Take off contaminated clothing and was before reuse.
<b>P391</b>	Collect spillage.
<b>Precautionary statement(s) Storage</b>	
<b>P405</b>	Store in locked up.
<b>Precautionary statement(s) Disposal</b>	
<b>P501</b>	Dispose of content/ container to appropriate waste site or reclaimer in accordance with local or national regulations.

SECTION 3 COMPOSITION / INFORMATION OF INGREDIENTS		
CAS number	% [weight]	Name
-	< 90	Resin
123-86-4	< 9	Butyl acetate
-	< 1	Additive

SECTION 4 FIRST AID MEASURES	
<b>Description of first aid measure</b>	
<b>Eye contact</b>	<ul style="list-style-type: none"> <li>Check or and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelid open. Do not use an eye ointment. Seek for medical attention.</li> </ul>
<b>Skin contact</b>	<ul style="list-style-type: none"> <li>Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an exiting dermatitis condition. Remove contaminated clothing – launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Get medical attention if redness or irritation occurs.</li> </ul>
<b>Inhalation</b>	<ul style="list-style-type: none"> <li>High vapour (&gt;1000 ppm) are irritating to the eyes and respiratory tract, may cause headaches, dizziness, anaesthesia. Drowsine unconsciousness and other central nervous system effects. Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform mouth to mouth resuscitation. Administer oxygen if available. Allow the victim to rest in a well ventilated area. Seek medical attention.</li> </ul>

SECTION 5 FIREFIGHTING MEASURES	
<b>Suitable Fire Extinguishing Media :</b>	
Small fire : Use dry powder, Foam.	
Large fire : Use water spray. Fog or foam. Water or foam may cause frothing.	
<b>Special Protective Actions For Fire Fighters:</b>	
Cool container in water spray in order to prevent pressure build-up, auto ignition or explosion. Avoid flushing spilled material into sewers, stream or other bodies of water. For small outdoor fires, portable fire extinguishers may be used, and self contained breathing apparatus (SCBA) may not be required. Respiratory and eye protection are required for fire fighting personnel.	
<b>Specific Hazards Arising From The Chemical :</b>	
Static discharge, material can accumulate static charges which can cause an incendiary electrical discharge. "Empty" containers retain product residue (liquid and/or vapour) and can be dangerous. DO NOT pressurize, cut. Weld braze, solder, drill grind, or expose such containers to heat, flame sparks, static electricity, or other sources of ignition ; they may explode and cause injury or death.	

<p><b>SECTION 6 ACCIDENTAL RELEASE MEASURES</b></p> <p><b>Personal Precautions, Protective Equipment And Emergency Procedure</b>                  Eye /skin protection :                  Where there is potential for eye contact, wear chemical goggles and have eye flushing equipment immediately available. Wear appropriate protective clothing and chemical resistant gloves to prevent skin contact. Wear a face shield and chemical resistant clothing such as rubber apron when splashing is likely.                  Respiratory Protection :                  Use JKKP/NIOSH approved respiratory protection (full face piece recommended) when exposure limits are exceeded.                  Ventilation :                  Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. If practical, use local mechanical exhaust ventilation at source of air contamination such as open process equipment.</p> <p><b>Environment Precaution</b>                  Flammable liquid. Ventilate. Eliminate all sources of ignition. Prevent additional discharge of material. For small spills implement cleanup procedure; for large spills implement cleanup procedure and if in public area, keep public away and advice authorities , provide suitable personal protective. dike and contain spill with inert material (sand, earth, etc) and transfer liquid and solid separately to container for recovery or disposal. Report as per regulatory or disposal. Do not use combustible material such as sawdust. Report as per regulatory equipment.</p> <p><b>Methods And Materials For Containments And Clean Up</b>                  For small liquid spills (&lt;1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residue to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose to all salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Remove contaminated soil and dispose of safely.</p>
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

<p><b>SECTION 7 HANDLING AND STORAGE</b></p> <p><b>Precautions For Safe Handling</b>                  Avoid smoking and use of open fire. Avoid inhalation of vapours and contact with skin and eyes. Observe good industrial practices.</p> <p><b>Condition For Safe Storage ,including Any Incompatibilities</b>                  Store in tightly closed original container in well-ventilated area. Avoid expose to direct sunlight.</p>
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

<p><b>SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION</b></p> <p><b>Control Parameters/ Occupational Limits</b></p> <table border="1"> <thead> <tr> <th rowspan="2">Ingredient/Bahan</th> <th colspan="2">ACGIH TLV-TWA</th> <th colspan="2">OSHA PEL-TWA</th> </tr> <tr> <th>ppm</th> <th>mg/m3</th> <th>ppm</th> <th>mg/m3</th> </tr> </thead> <tbody> <tr> <td>Butyl acetate</td> <td>150</td> <td>-</td> <td>150</td> <td>713</td> </tr> </tbody> </table> <p><b>APPROPRIATE ENGINEERING CONTROL MEASURES</b>                  If user operations generate dust, fumes, gas, vapours or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.                  Emission from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.</p> <p><b>PERSONAL PROTECTION</b>  <b>Respiratory protection</b>                  Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.                  Recommended : Full mask with type Cartridge filter.  <b>Hand protection</b>                  Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products I a risk assessment indicates this is necessary. After contamination with product change the gloves immediately and dispose of them according to relevant national and local regulations.  <b>Eye protection</b>                  Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.                  Recommended : Safety glasses with side-shields.  <b>Skin/ Body Protection</b>                  Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.                  Recommended : Wear protective clothing.</p>	Ingredient/Bahan	ACGIH TLV-TWA		OSHA PEL-TWA		ppm	mg/m3	ppm	mg/m3	Butyl acetate	150	-	150	713
Ingredient/Bahan		ACGIH TLV-TWA		OSHA PEL-TWA										
	ppm	mg/m3	ppm	mg/m3										
Butyl acetate	150	-	150	713										

<p><b>SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES</b></p> <table border="1"> <tr> <td><b>Appearance / colour</b></td> <td>Liquid/Clear</td> </tr> <tr> <td><b>Odour</b></td> <td>Aromatic Hydrocarbon</td> </tr> <tr> <td><b>Solid</b></td> <td>86-88%</td> </tr> <tr> <td><b>Specific Gravity (@ 25°C)</b></td> <td>1.04</td> </tr> <tr> <td><b>Viscosity (Ku)</b></td> <td>53 KU</td> </tr> <tr> <td><b>*Boiling Point</b></td> <td>123- 126 oC</td> </tr> <tr> <td><b>*Flash Point</b></td> <td>27 oC</td> </tr> <tr> <td><b>*Melting Point</b></td> <td>Not applicable</td> </tr> <tr> <td><b>*Vapour Pressure (@ 20°C)</b></td> <td>Not applicable</td> </tr> <tr> <td><b>Vapour Density (101.3 kPa / air=1)</b></td> <td>Not applicable</td> </tr> <tr> <td><b>Evaporation Rate (n - Butyl Ether=1)</b></td> <td>Not applicable</td> </tr> <tr> <td><b>Lower Flammable Limit LEL / Explosion limit (%)</b></td> <td>Not applicable</td> </tr> <tr> <td><b>Upper Flammable Limit UEL / Explosion limit (%)</b></td> <td>Not applicable</td> </tr> <tr> <td><b>Solubility</b></td> <td>Insoluble in water</td> </tr> </table>	<b>Appearance / colour</b>	Liquid/Clear	<b>Odour</b>	Aromatic Hydrocarbon	<b>Solid</b>	86-88%	<b>Specific Gravity (@ 25°C)</b>	1.04	<b>Viscosity (Ku)</b>	53 KU	<b>*Boiling Point</b>	123- 126 oC	<b>*Flash Point</b>	27 oC	<b>*Melting Point</b>	Not applicable	<b>*Vapour Pressure (@ 20°C)</b>	Not applicable	<b>Vapour Density (101.3 kPa / air=1)</b>	Not applicable	<b>Evaporation Rate (n - Butyl Ether=1)</b>	Not applicable	<b>Lower Flammable Limit LEL / Explosion limit (%)</b>	Not applicable	<b>Upper Flammable Limit UEL / Explosion limit (%)</b>	Not applicable	<b>Solubility</b>	Insoluble in water
<b>Appearance / colour</b>	Liquid/Clear																											
<b>Odour</b>	Aromatic Hydrocarbon																											
<b>Solid</b>	86-88%																											
<b>Specific Gravity (@ 25°C)</b>	1.04																											
<b>Viscosity (Ku)</b>	53 KU																											
<b>*Boiling Point</b>	123- 126 oC																											
<b>*Flash Point</b>	27 oC																											
<b>*Melting Point</b>	Not applicable																											
<b>*Vapour Pressure (@ 20°C)</b>	Not applicable																											
<b>Vapour Density (101.3 kPa / air=1)</b>	Not applicable																											
<b>Evaporation Rate (n - Butyl Ether=1)</b>	Not applicable																											
<b>Lower Flammable Limit LEL / Explosion limit (%)</b>	Not applicable																											
<b>Upper Flammable Limit UEL / Explosion limit (%)</b>	Not applicable																											
<b>Solubility</b>	Insoluble in water																											

**SECTION 10 STABILITY AND REACTIVITY****REACTIVITY**

No dangerous reaction known under condition of normal use.

**CHEMICAL STABILITY**

Stable under normal temperature conditions and recommended use.

**POSSIBILITY OF HAZARDOUS REACTION**

Under normal conditions of storage and use, hazardous reaction will not occur.

**CONDITIONS TO AVOID**

Heat, flame, sparks.

Nitric acid, sulfuric acid, strong oxidizing agents.

Electrostatic accumulation hazard? If Yes, use proper grounding procedure.

**HAZARDOUS DECOMPOSITION PRODUCTS**

When expose to high temperature, may produce hazardous decomposition products such as Carbon monoxide, carbon dioxide, smoke and oxides of nitrogen

**SECTION 11 TOXICOLOGY INFORMATION****There is no data available on the product itself.**

Toxicological information of hazardous ingredients :

**Acute toxicity /Ketoksikan Akut****Components/ Komponen:****Butyl Acetate:**

Acute oral toxicity : LD50 (Rat, male): 12,789 mg/kg

LD50 (Rat, female): 10,760 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): 0.74 mg/l

Acute dermal toxicity : LD50 (Rabbit): 14,000 mg/kg

**Skin corrosion/irritation****Components:**

Butyl Acetate:

Species : Rabbit

Exposure time: 4 h

Result : No skin irritation

**Serious eye damage/eye irritation****Components :**

Butyl Acetate:

Species : Rabbit

Result : No eye irritation

**Respiratory or skin sensitization****Components:**

Butyl Acetate:

Exposure routes: Inhalation

Remarks: No data available

Exposure routes: Skin contact

Result : Not sensitizing

**Germ cell mutagenicity****Components:**

Butyl Acetate:

Germ cell mutagenicity

Assessment: Not mutagenic in vivo and in vitro

**Carcinogenicity****Components:**

Butyl Acetate:

Carcinogenicity

Assessment : Not classified

**Reproductive toxicity****Components:**

Butyl Acetate:

Reproductive toxicity

Assessment : Not classified

**STOT - single exposure****Components:**

Butyl Acetate:

Target Organs : Central Nervous System

Assessment : May cause drowsiness or dizziness

**STOT - repeated exposure****Components:**

Butyl Acetate:

Remarks: Not classified

**Aspiration toxicity****Components:**

Butyl Acetate:

Statement on Aspiration Tox. : No data available

SECTION 12 ECOLOGICAL INFORMATION			
<b>Toxicity</b> No data available			
<b>Persistence and degradability</b> No information available.			
<b>Bioaccumulative Potential</b> Has the potential to bioaccumulate.			
<b>Mobility In Soil</b> Floats on water. Adsorbs to soil and has low mobility.			
<b>Other Adverse Effects</b> Do not allow product to reach ground water, water course or sewage system.			
Ingredient	Fish 96 hour, LC50 mg/L	Crustacea 48 hour, EC50 mg/L	Algae 72 or 96 hour, ErC50 mg/L
Butyl Acetate	18	44	397

SECTION 13 DISPOSAL INFORMATION
<b>Waste Disposal :</b> Recover or recycle if possible. Otherwise dispose in accordance with all applicable with all applicable national environment laws and regulations.
<b>Product Disposal:</b> This product when dispose of in its unused and uncontaminated state should be treated as a hazardous waste.
<b>Container Disposal :</b> Drain container thoroughly. Rinse three times with suitable solvent. Treat rinsing as for product disposal. After draining, vent in a safe place away from sparks and fire. Send drum recoverer or metal reclaimer. Residue may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums. Keep container labelled until cleaned and then remove or deface labels.

SECTION 14 TRANSPORT INFORMATION
Transport to be in accordance with ADR/RID for road/rail, IMDG for sea and IATA for air.
<b>LAND TRANSPORT</b> Classified as Dangerous Goods by the criteria of the European Agreement concerning the international carriage of Dangerous Goods (ADR) by Road & Regulations concerning the international carriage of Dangerous Goods (RID) by Rail.
<b>UN Number:</b> 1263 Proper shipping name : Paint ( including paint, lacquer, enamel, stain, shellac, varnish, liquid filler and liquid lacquer base ) or paint related material (including paint thinning or reducing compound. <b>Class:</b> 3 <b>Packaging Group:</b> III
<b>SEA TRANSPORT</b> Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG) for the transport of Sea.
<b>UN Number:</b> 1263 Proper shipping name : Paint ( including paint, lacquer, enamel, stain, shellac, varnish, liquid filler and liquid lacquer base ) or paint related material (including paint thinning or reducing compound. <b>Class :</b> 3 <b>Packaging Group:</b> III <b>Marine Pollutant:</b> No <b>SEA (Annex II of MARPOL 73/78 and the IBC Code)/ LAUT (Annex II of MARPOL 73/78 dan the IBC Code) :</b> Not Applicable
<b>AIR TRANSPORT</b> Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for the transport by Air.
<b>UN Number:</b> 1263 <b>Proper shipping name :</b> Paint ( including paint, lacquer, enamel, stain, shellac, varnish, liquid filler and liquid lacquer base ) or paint related material (including paint thinning or reducing compound. <b>Class:</b> 3 <b>Packaging Group:</b> III

**SECTION 15 REGULATORY INFORMATION**

Applicable national regulations :

- a) OSHA 1994 and relevant regulation
- b) Factories and Machinery Act 1967 and relevant regulations
- c) Environment Quality Act 1967 and regulations.
- d) Pesticide Act 1974 and regulations
- e) Occupational Safety and Health (Classification, Labelling And Safety Data Sheet of Hazardous Chemicals) Reg 2013
- f) Industry Code Of Practice (On Chemicals Classification And Hazard Communication

**SECTION 16 OTHER INFORMATION**

Date of preparation: 05-06-2024  
Date of revision: -  
Version: 01

**ABBREVIATION/SINGKATAN**

ACGIH American Conference of Governmental Industrial Hygienists  
TLV Threshold limit value  
TWA Time-Weighted Average  
OSHA Occupational Safety and Health Administration  
PEL Permissible Exposure Limit  
LD50 Lethal Dose  
LC50 Median Lethal concentration  
IACR International Agency for Research in Cancer  
CAS Registry Numbers Chemical Abstracts Service Registry Numbers  
ICOP Industry Code Of Practice on Chemical Classification and Health approved by Minister under section 37 of the Act  
C Ceiling Limit  
CEIL Ceiling Limit airborne concentration  
STEL Short Term Exposure Limit  
DNA Data Not Available  
N/R Not Regulated

**Disclaimer**

All information appearing here in is based on our present state of our knowledge. However the information in this SDS may not be valid for such material used in combination with any other materials or in any process. No representation, warranty or guarantee is made as to its accuracy, reliability or completeness. We do not accept liability for any loss or damage that may occur from the use of this information.