



## Smart Fresh Air A+ Classe

SPFAA+CLASSE/SPTBFAA+CLASSE

1 litre, 5 litres & 15 litres

### Description

Smart Fresh Air A+ Classe is a premium eco and health friendly interior paint specially formulated for easy cleaning. This low odour, near zero VOC formula provides a tough and extremely smooth surface for easy cleaning. Stains can be easily wiped off, so the egg-shell finish walls are always clean and easy to maintain. Smart Fresh Air A+ Classe is formulated to resist spattering to help keep tools and jobsite clean, application will always flow smooth for perfect finishing.

Note : Volatile organic compound (VOC) are air borne chemicals harmful to health and the environment

### Usage

For decoration and protection of wall, ceiling, plaster, brickwork and cement board for a Smooth and Elegant Classic egg shell finish.

### Composition

Pigment	:	Lightfast non-lead pigments and mineral extenders
Binder	:	Vinyl Acetate - Ethylene emulsion.
Volume Solid	:	White 42% (Nominal), other colours will vary.
Diluent	:	Water

### Properties

Finishing	:	Smooth Elegant Classic Egg Shell Finish.
Colour	:	Refer to color card.
Theoretical Coverage	:	9 - 11m <sup>2</sup> / Litre (actual coverage dependent on substrate condition.)
Drying Time	:	Touch dry – 15 minutes (Dependent on temperature and humidity)
Recoating Interval	:	1 to 2 hours

### Application Method

Brush	:	For normal use thinning is not usually necessary.
Roller	:	For normal use thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application
Conventional Air Spray	:	Thin with max 10 – 20 % by volume with water
Airless Spray	:	For normal use thinning is not usually necessary. Can be thin with 5 – 10% by volume with water to assist application

## Surface Preparation

### General/New

Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. To have better finish rubbed down surface using suitable abrasive and dust off. If after thorough preparation surface remain powdery, or suffer from alkali attack, for best effect seal with 1 coat of Smart Fresh Air A+ Seale.

### Previously Painted Surface

Remove all loose, defective and unstable paint film or powdery residues by thorough brushing and scraping. Make good minor defects and cracks with suitable grade filler.

## Painting Guide

Surface	Primer (To paint 1 coat)	Finish (To paint 2 - 3 coats)
Powdery surface	<ul style="list-style-type: none"> <li>• Smart GP Wall Sealer 400</li> <li>• Smart Wall Sealer 800</li> <li>• Smart Fresh Air A+ Seale</li> <li>• Smart Green Sealer 850</li> <li>• Smart Wall Sealer 900</li> </ul>	Smart Fresh Air A+ Classe
Alkaline/ New surfaces	<ul style="list-style-type: none"> <li>• Smart Wall Sealer 800</li> <li>• Smart Fresh Air A+ Seale</li> <li>• Smart Green Sealer 850</li> <li>• Smart Wall Sealer 900</li> </ul>	Smart Fresh Air A+ Classe

## Company Identification

Manufacturer : Smart Paint Manufacturing Sdn. Bhd.  
 No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,  
 81800 Ulu Tiram, Johor, Malaysia  
 Telephone No. : +607-863 9855 (Hunting Line) Fax No. : +607-861 5055  
 Email : info@smart-paints.com