



Smart Fresh Air A+ Eco Wall

SPFAA+ECW/SPTBFAA+ECW

1 litre, 5 litres & 15 litres



Description

Smart Fresh Air A+ Eco Wall is specially formulated healthy friendly emulsion paint for interior masonry. It provides an attractive smooth matt finish on walls, asbestos, hard and soft boards. This product is low odour and contains near zero volatile organic compounds (VOC)—chemicals given off by paints that have been linked to respiratory illnesses. It is highly recommended for housing scheme and where economy is priority.

Usage

For decoration and protective of wall, ceiling, plaster, brickworks, cement board, hard and soft board.

Composition

Pigment	:	Lightfast non-lead pigments and mineral extenders
Binder	:	Vinyl Polymer
Volume Solid	:	37% (nominal), other colour will be vary.
Diluent	:	Water

Properties

Finishing	:	Classic matt finish
Colour	:	Refer to Smart Smartex Eco Wall colour card
Theoretical Coverage	:	10 - 13m ² / Litre (actual coverage dependent on substrate condition.)
Drying Time	:	Touch dry – 15 - 30minutes (Dependent on temperature and humidity) Hard dry – 1 hour (Dependent on temperature and humidity)
Recoating Interval	:	1 to 2 hours

Application Method

Brush	:	Thin with 5 - 10% by volume with water.
Roller	:	Thin with 5 - 10% by volume with water.
Conventional Air Spray	:	Thin with max 10 – 20 % by volume with water
Airless Spray	:	Thin with max 10 – 20 % by volume with water

Surface Preparation

- Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease and wax. (To have a better finish, rub down surface using suitable abrasive and dust off.)
- If after thorough preparation surface remains powdery, for best effect seal with 1 coat of Smart Fresh Air A+ Seale. If the surface suffers from alkali attack, it is best recommended to seal with 1 coat of Smart Fresh Air A+ Seale.

Painting Guide

Surface	Primer (To paint 1 coat)	Finish (To paint 2 - 3 coats)
Powdery surface	<ul style="list-style-type: none"> • Smart Fresh Air A+ Seale 	Smart Fresh Air A+ Eco Wall
Alkaline/ New surfaces	<ul style="list-style-type: none"> • Smart Fresh Air A+ Seale 	Smart Fresh Air A+ Eco Wall

Company Identification

Manufacturer : Smart Paint Manufacturing Sdn. Bhd.
 No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,
 81800 Ulu Tiram, Johor, Malaysia
 Telephone No. : +607-863 9855 (Hunting Line) Fax No. : +607-861 5055
 Email : info@smart-paints.com