

Smart Smartex Eco Wall

SPECW

1, 5 & 18 Litres



Description

Smartex Eco Wall is specially formulated healthy friendly emulsion paint for interior masonry. It provides an attractive smooth matt finish on walls, asbestos, hard and soft boards. This product is low odour and contains near zero volatile organic compounds (VOC)—chemicals given off by paints that have been linked to respiratory illnesses. It is highly recommended for housing scheme and where economy is priority.

Usage

For decoration and protective of wall, ceiling, plaster, brickworks, cement board, hard and soft board.

Composition

Pigment	:	Lightfast non-lead pigments and mineral extenders
Binder	:	Vinyl Polymer
Volume Solid	:	43% (nominal), other colour will be vary.
Diluent	:	Water.

Properties

Finishing	:	Classic matt finish
Colour	:	Refer to Smart Smartex Eco Wall colour card
Theoretical Coverage	:	10 – 13 m ² /Litre (actual coverage dependent on substrate condition.)
Drying Time	:	*Touch dry – 15 to 30 minutes. *Hard dry – 1 hour. *Dependent on temperature and humidity.
Recoating Interval	:	1 to 2 hours.

Application Method

Brush	:	Thin with 5 - 10% by volume with water.
Roller	:	Thin with 5 - 10% by volume with water.
Conventional Air Spray	:	Thin with 10 – 20% by volume with water.
Airless Spray	:	Thin with 10 – 20% by volume with water.

Surface Preparation

Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease and wax. (To have a better finish, rub down surface using suitable abrasive and dust off.) If after thorough preparation surface remains powdery, for best effect seal with 1 coat of Smart Eco Sealer. If the surface suffers from alkali attack, it is best recommended to seal with 1 coat of Smart Eco Sealer.

Painting Guide

Substrate	Primer (1coat)	Finish (2 coats)
Powdery Surface	<ul style="list-style-type: none"> • Smart Eco Sealer 	Smart Smartex Eco Wall
Alkali/ New Surface	<ul style="list-style-type: none"> • Smart Eco Sealer • Smart Base Coat Sealer 	Smart Smartex Eco Wall

Company Identification

Manufacturer : Smart Paint Manufacturing Sdn. Bhd.
 No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,
 81800 Ulu Tiram, Johor, Malaysia
 Telephone No. : +607-863 9855 (Hunting Line) Fax No. : +607-861 5055
 Email : info@smart-paints.com