



Smart Exterior Granite (2 pack system Polyurea Floor)

SPEG

20Kg (Part A:15kg + Part B:5kg)

4Kg (Part A:3kg + Part B:1kg)



Description

SMART EXTERIOR GRANITE is a 2K self-levelling polyurethane flooring system that uses advanced colour floating sand technology to achieve elegant, granite-like decorative surfaces. Designed for superior aesthetics and performance, it offers a versatile range of colours and pattern with outstanding compressive strength, slip resistance, and long-term durability against abrasion and chemicals. Ideal for industrial, commercial, and residential spaces, Smart Exterior Granite delivers a modern, premium finish with a faster and more efficient application process.

Usage

Smart ExteriorGranite is painted as a topcoat on exterior flooring.

Composition

Pigment	:	Mineral Extenders
Binder	:	High solid polyurethane
Volume Solid	:	100%

Properties

Finishing	:	Smooth granite-like surfaces
Colour	:	Light grey, Medium grey, Purple grey, Tiny grey, Pink, Green, Brown,
Theoretical Coverage	:	0.5 m ² /kg (actual coverage dependent on
Pot Life	:	30 minutes
Drying Time	:	Touch Dry: About 4 hours (Dependent on temperature and humidity and thickness applied)
	:	Hard Dry: About 9 hours (Dependent on temperature and humidity and thickness applied)
Recoating Interval	:	8 hours minimum based on normal condition

Surface Preparation

Remove all loose, defective paint or powdery residues, loose chalk, dust and foreign matter. Repair cracks, uneven surfaces with suitable fillers. Smoothen the putty / filler areas with sand paper. Surfaces to be painted must be cleaned thoroughly and dry, it must be free from dirt, grease and other foreign matters. Allow all surfaces to dry completely prior to painting. Avoid painting when the moisture content and alkalinity of the walls are still high. (Recommended painting specification requires the moisture content of the walls to be below 16% measured by protimeter and alkalinity of the walls to be below pH 9.)

Painting Guide

Preparation	Sealer/Primer	Intermediate	Finish (1 coat)
For Recoat Floor Surface with previous coating cleaned	Smart Epoxy Granite Primer	-	Smart Exterior Granite
New cement floor surfaces	Smart Epoxy Granite Primer	-	Smart Exterior Granite

Company Identification

Manufacturer : Smart Paint Manufacturing Sdn. Bhd.
 No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,
 81800 Ulu Tiram, Johor, Malaysia
 Telephone No. : +607-863 9855 (Hunting Line) Fax No. : +607-861 5055
 Email : info@smart-paints.com